

Emergency Lighting / Emergency Lighting

Spectrum 3W LED Emergency Open Area Downlight - Non-Maintained - Select Self-Test or Manual Emergency Mode



The 3W Spectrum Non Maintained Downlights have a dual colour charge indicator and come complete with a battery pack enclosed in a protective housing. This IP20 rated fixture can be purchased for both Open Area and Corridor applications.

- Selectable Self-Test or Manual Emergency Mode.
- Open Area/Corridor versions.
- Dual colour charge indicator.
- Complete with driver and fire-rated battery pack.
- 3W recessed.

Technical Specification

| | |
|--------------|---------|
| Product Code | 09030V2 |
|--------------|---------|

Reference

| | |
|-------------------|---------------|
| Guarantee | 5 Years |
| EAN | 5013588900100 |
| Commodity Code | 8513100000 |
| Country of Origin | CN |

Technical Specification

| | |
|--------------------------------|---------|
| Volts (V) | 220/240 |
| Watts (W) | 3 |
| Colour Temp (K) | 6500 |
| Dimmable? | No |
| Lumens (lm) | 150 |
| Candelas (cd) | 12 |
| Life Hours | 25000 |
| Beam Angle | 120° |
| CRI (ra) | 72 |
| Switching Cycles | 12500 |
| Frequency (Hz) | 50/60 |
| LED Drive Current | 500mA |
| Energy Consumption (kWh/1000h) | 3 |
| IP Rating | IP20 |
| Impact Protection | IK5 |

Dimensions

| | |
|------------------------|----|
| Height (mm) | 29 |
| Width (mm) | 30 |
| Depth (mm) | 22 |
| Diameter (mm) | 42 |
| Downlight Cut Out (mm) | 34 |

Packaging Information

| | |
|---------------------------|--------|
| Single Carton Height (mm) | 90 |
| Single Carton Width (mm) | 200 |
| Single Carton Depth (mm) | 50 |
| Single Carton Weight (kg) | 0.2 |
| Individual Volume | 0.0009 |
| Outer Box Qty | 20 |
| Outer Box Height (mm) | 210 |
| Outer Box Width (mm) | 380 |
| Outer Box Depth (mm) | 230 |
| Outer Box Weight (kg) | 4.2 |