

Choice PR1n 1 Channel Programmer



Benefits

The Choice PR1 is a single channel programmer, designed primarily for timed control of your heating and hot water. Ideal for use with a combination (combi) boiler.

The programmer can be configured for 24 hour, 5/2 day or 7 day operation, and the flexibility of up to three on/off timings per day.

- Pre-programmed but can easily be changed to suit your particular lifestyle
- Large and clear to read illuminated display
- Attractive modern design that will suit all contemporary homes
- Ideal for use with "Combination" Boilers with only one heating zone
- Can also be used in conjunction with an existing programmer to control additional heating zones or for when additional hot water cylinder control is required

Features

- 24 hour, 5/2 day and 7 day selectable
- 2 or 3 ON/OFF periods selectable
- 1,2 or 3 hour boost
- Advance to next programmed event
- Automatic Summer/Winter time change

Applications

• Any simple time switch application up to the stated rating.

• Domestic heating systems where both heating and hot water services are required to switch ON/OFF at the same time.

٠

• Controlling a "Combi" or "Combination Boiler"



Factory set time & date Program options - ON, OFF, All day or Auto

- Mains powered with battery backup
- Standard wall plate simple plug in and replace


sangamo.co.uk

Technical Data

Program Selection:Auto, On all day, On constant, onProgram Override:1, 2 or 3 hour, AdvanceHeating System:PumpedComplies with :EN60730-1, EN60730-2.7, EMC Directive 2004/108/EC,	Program resolution:10minsProgram Selection:Auto, On all day, On constant, off	Program Selection: Program Override: Heating System:	Automatic 24hr, 5/2day or 7day selectable. 2on/off, 3on/off selectable, 10mins Auto, On all day, On constant, off 1, 2 or 3 hour, Advance Pumped
Complies with : EN60730-1, EN60730-2.7, EMC Directive 2004/108/EC, LVD Directive 2006/95/EC		Complies with :	
LVD DIRECTIVE 2006/95/EC	Heating System:PumpedComplies with :EN60730-1, EN60730-2.7, EMC Directive 2004/108/EC,		LVD DIRECTIVE 2006/95/EC
	Heating System:PumpedComplies with :EN60730-1, EN60730-2.7, EMC Directive 2004/108/EC,		
-		0	
Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10mins			
Program Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10mins	Program Cycle: 24hr, 5/2day or 7day selectable.		
BST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10mins	BST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.		
Clock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10 mins	Clock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.	•	
Dimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10 mins	Dimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.	Wiring:	For fixed wiring only
Backplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10 mins	Backplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.	Insulation Class:	• •
Wiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10 mins	Wiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.		Thermoplastic, flame retardant
Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10 mins	Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.	5 51	
Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10mins	Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.		
Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program On/offs per day:2on/off, 3on/off selectable,Program resolution:10mins	Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.	•	
Contact Type:1B , Micro-Disconnection (Voltage Free)Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.Program resolution:10mins	Contact Type:1B , Micro-Disconnection (Voltage Free)Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.		
Total Switch Rating:230V AC, 6(2)A (Total)Contact Type:1B, Micro-Disconnection (Voltage Free)Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram On/offs per day:20n/off, 30n/off selectable,Program resolution:10mins	Total Switch Rating:230V AC, 6(2)A (Total)Contact Type:1B, Micro-Disconnection (Voltage Free)Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.		•
Operating Temperature:0°C to 35°CTotal Switch Rating:230V AC, 6(2)A (Total)Contact Type:1B, Micro-Disconnection (Voltage Free)Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dayBST/GMT time change:AutomaticProgram On/offs per day:2on/off, 3on/off selectable,Program resolution:10mins	Operating Temperature:0°C to 35°CTotal Switch Rating:230V AC, 6(2)A (Total)Contact Type:1B , Micro-Disconnection (Voltage Free)Battery Type:Lithium Cell CR2032Enclosure Protection:IP30Plastics:Thermoplastic, flame retardantInsulation Class:DoubleWiring:For fixed wiring onlyBackplate:Industry standardDimensions:140mm x 87mm x 37mmClock:12 hour am/pm, 1 minute resolution, accuracy +/- 2 sec/dBST/GMT time change:AutomaticProgram Cycle:24hr, 5/2day or 7day selectable.	Devices Consults	

Electrical Connections

Internal Wiring Diagram



Technical Helpline: 01475 745131

CUSTOMER CARE POLICY

As part of Sangamo's continuous improvement program, the Company operates a Customer Care Policy. This means that we welcome your comments and complaints, as it can only help us to improve our services to you, our customer.





Sangamo Limited, Industrial Estate, Port Glasgow, Renfrewshire PA14 5XG Tel: 01475 745131 Fax: 01475 744567 Email : enquiries@sangamo.co.uk Web: www.sangamo.co.uk

SAN0101-B_2014