

**SHARK Range, Smart SHARK and SHARK Classic Series**

# SHARK



## Smart SHARK

<b>Material</b>	Polyamide
<b>Filling</b>	Silicone gel
<b>Temperature range</b>	-20 °C · 90 °C
<b>Glow wire test</b>	Self-extinguishing
<b>Voltage</b>	0.6 kV · 1 kV
<b>Colour</b>	Blue
<b>Included</b>	Terminal block



Smart SHARK

**SHARK, Smart SHARK**

Type	WISKA-No.	Description		Amp	LxBxH Innen (mm)	
SHARK 315W	SH0315W	Pre-filled gel insulated joint	3	5	40 x 72 x 23	1
SHARK 325W	SH0325W	Pre-filled gel insulated joint	3	6	47 x 86 x 27	1
SHARK 310W	SH0310W	Pre-filled gel insulated joint	3	13	55 x 146 x 35	1
SHARK 316W	SH0316W	Pre-filled gel insulated joint	3	30	69 x 180 x 40	1

# SHARK

## SHARK Classic Series




<b>Material</b>	Polyamide
<b>Filling</b>	Silicone gel
<b>Temperature range</b>	-20 °C · 90 °C
<b>Glow wire test</b>	Self-extinguishing
<b>Voltage</b>	0.6 kV · 1 kV
<b>Colour</b>	Blue
<b>Included</b>	Terminal block, earth braid and spring coil.
<b>Additional info</b>	Complies with EN50393 for underground joints.



SHARK Classic Series

Suitable for  
Steel Wired  
Armour Cables

**SHARK, SHARK Classic Series**

Type	WISKA-No.	Description		Amp	 (mm)	LxBxH Innen (mm)	
SHARK 506W	SH506W	Pre-filled gel insulated joint	5	80	1.5 · 6	55 x 146 x 35	1
SHARK 525W	SH525W	Pre-filled gel insulated joint	3	135	2.5 · 16	69 x 180 x 40	1
			4		2.5 · 16		
			5		2.5 · 10		