

technical hotline +44 (0)1268 563720

decorative | wiring devices

Switchsocket Outlets

13 AMP

1 GANG DP
DUAL EARTH
TERMINALS
FLUSH

2 GANG DP
FLUSH

2 GANG DP WITH
RED ROCKERS
FLUSH

1 GANG DP
DUAL EARTH
TERMINALS
WITH NEON
FLUSH



FINISHES

BRUSHED STAINLESS STEEL	K2958BSS	10	K2948BSS	5	K2948D6BSS	5	K2458BSS	10
BRUSHED CHROME	K2958BRC	10	K2948BRC	5	K2948D6BRC	5	K2458BRC	10
SATIN GOLD	K2958SAG	10	K2948SAG	5			K2458SAG	10
POLISHED CHROME	K2958PCR	10	K2948PCR	5			K2458PCR	10

High Integrity Earthing
K2958, K2458, K2947
Fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671: 2008

High Integrity Earthing
K2958, K2458, K2947
Fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671: 2008.

MOUNTING BOXES:

FLUSH 25mm
1 GANG: 861ZIC
2 GANG: 862ZIC
FLUSH 35mm (for extra wiring space)
1 GANG: 866ZIC
2 GANG: 886ZIC

SURFACE WITH KNOCKOUTS

1 GANG: K899ALM
2 GANG: K897ALM

SURFACE WITHOUT KNOCKOUTS

1 GANG: K829ALM
2 GANG: K830ALM

DIMENSIONS:

1 GANG: 86 x 86mm
2 GANG: 86 x 146mm

FIXING CENTRES:

1 GANG: 60.3mm
2 GANG: 120.6mm

BS 1363 Pt 2: 1995

Double pole switching

All switchsockets have double pole switching (neutral makes first, breaks last).