

technical hotline +44 (0)1268 563720

decorative | wiring devices

1 GANG SP
TWO-WAY
10 AMP
WIDE ROCKER
FLUSH

2 GANG SP
TWO-WAY
WIDE ROCKER
FLUSH

3 Pole Fan Isolator

10 AMP
WITHOUT
SWITCHLOCK
FLUSH

SWITCHLOCK
FOR FAN
ISOLATOR

Standard Dimmer Switches

230Va.c. 50Hz TUNGSTEN FILAMENT

1 GANG TWO WAY
SINGLE
40W MIN, 250W
MAX
FLUSH

1 GANG TWO WAY
SINGLE
60W MIN,
500W MAX
FLUSH



K4761BSS	5	K4762BSS	5	K4860BSS	1	K4858	10	K1534BSS	1	K1551BSS	1
K4761BRC	5	K4762BRC	5	K4860BRC	1		K1534BRC	1	K1551BRC	1	
K4761SAG	5	K4762SAG	5	K4860SAG	1		K1534SAG	1	K1551SAG	1	
K4761PCR	5	K4762PCR	5	K4860PCR	1		K1534PCR	1	K1551PCR	1	

MOUNTING BOXES:

FLUSH: 3995ZIC

SURFACE: K2160WHI

For local isolation of fans with or without timers for repair or routine maintenance.

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS EN 60947-3: 1992

Conforming to the latest standards BS EN 60669-2-1 and BS EN 55015, they are overload protected and are suitable for use with tungsten filament lamps only.

Two way dimmers use push on/push off switches.

They are not suitable for use with fluorescent loads or with electronic or with wire-wound transformers in low voltage lighting systems.