## 206

# Ancillary Products

### wiring devices | boxes and ancillary products



#### www.mkelectric.co.uk

Fuse-Links						Additional Sc	rews
BS 646:1958 250V 50-60 Hz		BS 1361:1971 250 V. 50-60Hz		BS 1362:1973 250V 50-60Hz		1015MBRS* SCREW 5BA 10mm 1015MNIP* SCREW 5BA 10mm	100 100
K600 K630 K630 K602 K601	1	Image: Second		134   K610   34   K612   104   104   104   105   104   105   104   105   105   105   105   106   107   108   109   109   1000 </td <td></td> <td>1045ABRS* SCREW 5BA 18mm TAMP 1045ANIP* SCREW 5BA 18mm TAMP 11130NIPMA* SCREW M3.0 12mm 11135NIPMA SCREW M3.5 14mm 11135NIPMB SCREW M3.5 14mm 11135NIPMB SCREW M3.5 22mm 11135BRSME SCREW M3.5 24mm 11135BRSME SCREW M3.5 32mm 11135BRSMF SCREW M3.5 32mm 11135BRSMF SCREW M3.5 40mm 11135BRSMG SCREW M3.5 40mm</td> <td>100</td>		1045ABRS* SCREW 5BA 18mm TAMP 1045ANIP* SCREW 5BA 18mm TAMP 11130NIPMA* SCREW M3.0 12mm 11135NIPMA SCREW M3.5 14mm 11135NIPMB SCREW M3.5 14mm 11135NIPMB SCREW M3.5 22mm 11135BRSME SCREW M3.5 24mm 11135BRSME SCREW M3.5 32mm 11135BRSMF SCREW M3.5 32mm 11135BRSMF SCREW M3.5 40mm 11135BRSMG SCREW M3.5 40mm	100
<b>K600</b> 5A RED	10	<b>K606</b> 30A RED	10	K610 13A BROWN*	10	SCREW M4.0 20mm 11430BRSMA* SCREW M3.0 12mm TAMI	100 PERPROOF
<b>K630</b> 3A BLACK	10	K603 20A YELLOW	10	K612 3A RED*	10	11430NIPMA* SCREW M3.0 12mm TAM	
K602 2A YELLOW	10	K605 15A BLUE	10	K609 10A BLACK #	10	11435BRSME SCREW M3.5 35mm TAMI 11435NIPME	100 PERPROOF 100
<b>K601</b> 1A GREEN	10	<b>K604</b> 5A WHITE	10	<b>K608</b> 5A BLACK#	10	SCREW M3.5 35mm TAM 11435NIPMJ	PERPROOF
				<b>K607</b> 2A BLACK#	10	SCREW M3.5 29mm TAMI 645NIP	PERPROOF 100

lditional Sc	rews	Additional Edge and Aspect Screws			
15MBRS*	100				
W 5BA 10mm	100	SCREW M3.0 12mm (2 SCREWS/PKT) 48370SSPBRT9			
15MNIP* W 5BA 10mm	100	48370SSPBRT9 100 SCREW M3.0 12mm (2 SCREWS/PKT)			
45ABRS*	100	48370SSBLKT9			
W 5BA 18mm TAMP		SCREW M3.0 12mm (2 SCREWS/PKT)			
45ANIP	100	48370SSNIPT9			
W 5BA 18mm TAMP	STORY CALL STREET	SCREW M3.0 12mm (2 SCREWS/PKT)			
130NIPMA*	100	483705SWHIT9 100			
W M3.0 12mm	19 <del>10 (1910)</del> 1911 - State	SCREW M3.0 12mm (2 SCREWS/PKT)			
135NIPMA*	100	48370SSPBRT9			
W M3.5 14mm		SCREW M3.0 12mm (2 SCREWS/PKT)			
135NIPMB	100	48370SSPBZT9			
W M3.5 22mm		SCREW M3.0 12mm (2 SCREWS/PKT)			
135NIPMC	100	43066SSNIPT9 100			
EW M3.5 24mm		SCREW M3.5 22mm (2 SCREWS/PKT)			
135BRSME	100	43066SSPBRT9			
W M3.5 32mm	100	SCREW M3.5 22mm (2 SCREWS/PKT)			
135NIPME	100	43066SSWHIT9			
W M3.5 32mm	100	SCREW M3.5 22mm (2 SCREWS/PKT) 43066SSBLKT9			
135BRSMF W M3.5 40mm	100	430665SBLKT9 100 SCREW M3.5 22mm (2 SCREWS/PKT)			
135NIPMF	100	43066SSPBZT9			
W M3.5 40mm	100	SCREW M3.5 22mm (2 SCREWS/PKT)			
135BRSMG	100	43352SSNIPT9			
W M3.5 48mm		SCREW M3.5 28mm (2 SCREWS/PKT)			
135NIPMG	100	43352SSPBRT9 100			
W M3.5 48mm	Januaran.	SCREW M3.5 28mm (2 SCREWS/PKT)			
135BRSMK	100	43352SSWHIT9 100			
W M3.5 29mm	1005.000	SCREW M3.5 28mm (2 SCREWS/PKT)			
135NIPMK	100	43352SSBLKT9 100			
W M3.5 29mm		SCREW M3.5 28mm (2 SCREWS/PKT)			
135NIPMN	100	43352SSPBZT9 100			
W M3.5 25mm	100	SCREW M3.5 28mm (2 SCREWS/PKT)			
140NIPMA	100				
W M4.0 20mm	100				
430BRSMA* W M3.0 12mm TAM	100 PERPROOF				
430NIPMA*	100				
W M3.0 12mm TAM		Decile contract			
435BRSME	100	Replacement			
W M3.5 35mm TAMPERPROOF		Components			
435NIPME	100				
W M3.5 35mm TAM	PERPROOF	3405710 10			

DIMENSIONS: Overall length 19.1mm +0.8mm -0.4mm End-cap diameter 5.3mm +0.1mm -0.1mm End-cap length 4.0mm +0.8mm -0.8mm

K606 Overall length 29.0mm +0.4mm -0.4mm End-cap diameter 12.7mm +0.1mm -0.1mm End-cap length 8.0mm +0.5mm -0.5mm K604 Overall length 23.0mm +0.0mm -0.8mm End-cap diameter 6.35mm +0.1mm -0.1mm End-cap length 4.8mm +0.5mm -0.5mm K603, K605 Overall length 26.0mm +0.2mm -0.6mm End-cap diameter 10.32mm +0.1mm-0.1mm End cap length 6.4mm +0.5mm -0.5mm

\*These ratings are for use with plugs complying with BS 1363, fused connections units and similar accessories. #These ratings are for use with fused connection units and similar accessories. DIMENSIONS: Overall length 25.4mm +0.8mm -0.4mm End-cap diameter 6.3mm +0.2mm -0.5mm End-cap length 5.5mm +0.8mm -0.8mm

SECRET SCREW for use with 646, 655 & 647 644ZIC **KEY FOR 645NIP** 

3400ZIC

10 TAMPERPROOF KEY

BRS finish for use with SAG accessories. NIP finish for use with BRC, ALM, PCR

Tamperproof screws include one key

"For use with old Grid System

\*\* For use with Grid Plus

and WHI accessories.

per pack.

10

SCREW CONNECTION UNITS

DUAL USE KEY FOR TAMPER

PROOF KEY SWITCH AND SECRET

#### 6084SLWHI

3405ZIC



FUSE CARRIERS for all Clock Connectors supplied with fuse

1

10