

technical hotline +44 (0)1268 563720

boxes and ancillary products | wiring devices

## Terminal Blocks

## Service Connector Boxes

## Accessories For Boxes

## Neon Lamp Assemblies



913BRO



914BRO



1100BLK



1101BLK



3714

3715



3710



800ZIC



3840ZIC



5144SS000T9

17270SS

**913BRO**  
3 WAY

5

**914BRO**  
4 WAY

5

**1100BLK**  
5 WAY DOUBLE POLE  
100A

10

**1101BLK**  
5 WAY SINGLE POLE  
100A

10

**3714**  
BRASS EARTH  
TERMINAL WITH BRACKET

100

**3715**  
BRASS EARTH  
TERMINAL  
SCREW FIX ANGLED

100

**3709**  
BRASS EARTH  
TERMINAL  
SCREW FIX STRAIGHT

100

**K3716**  
BRASS EARTH  
TERMINAL

100

**3710**  
EXTENSION STUD.  
M3.5  
Zinc-plated steel.  
Overall length 34mm

100

**800ZIC**  
BOX FIXING FLANGE  
Use two to mount any flush  
MK box in a dry-partition wall

20

**3840ZIC**  
CONVERSION BRACKET  
Complete with earth terminal.  
Converts 25mm deep flush  
switch boxes with 42mm  
fixing centres to accommodate plateswitches  
with 60.3mm  
fixing centres

10

**5144SS000T9**  
LAMP LEAD AND  
RESISTOR ASSEMBLY  
For Ceiling Switch blocks  
and 32A DP switches

1

**17270SS**  
LAMP LEAD AND  
RESISTOR ASSEMBLY  
Tag ended neon for use with  
45, 50A switches and  
cooker units

10

**7179PS**  
MALE CONNECTOR  
For Switchsockets

10

### TERMINAL CAPACITY

913: Each terminal accepts up to 3 x 2.5mm<sup>2</sup> (solid conductors) or 3 x 4mm<sup>2</sup> (stranded conductors).

914: Each terminal accepts up to 4 x 1.5mm<sup>2</sup> conductors.

**FIXING CENTRES:**  
60.3mm for mounting on 'spare' lugs of 4 or 6 lug BS 4662 boxes.

### TERMINAL CAPACITY

All 25mm<sup>2</sup>

Where it is necessary to take the outer sheath of a double insulated cable into the box, the cable sizes are restricted to 16mm<sup>2</sup>.

**DIMENSIONS (OVERALL)**  
1100 BLK 65 x 89 x 60mm  
1101 BLK 47 x 64 x 41mm

BS 7657: 2010