

technical hotline +44 (0)1268 563720

decorative | wiring devices

Euro Blank Modules

EURO
TWO MODULE
(50 X 50MM)

EURO
ONE MODULE
(25 X 50MM)

EURO
1/2 MODULE
(12.5 X 50MM)







LJU6C Datacom Frontplate

1 GANG
TWO MODULE
22 X 37MM

LJU6C Datacom Modules

RJ11/12
ONE MODULE

RJ45 CAT 6
ONE MODULE

					
K180WHI 10	K188WHI 10 K188BLK 10	K186WHI 10 K186BLK 10	K14172BSS 10 K14172LBS 10 K14172SAA 10 K14172BRC 10 K14172POC 10 K14172SAG 10 K14172WHI 10 K14172LIV 10 K14172LBK 10 K14172PBR 10 K14172TIR 10 K14172DBZ 10 K14172ABS 10 K14172TCO 10	K5787WHI 5 K5787BLK 5	K5746WHI 5 K5746BLK 5

MOUNTING BOXES:
Min. box depth 16mm
BS 5733: 2010 where applicable

MOUNTING BOXES:
Min. box depth 16mm
BS 5733: 2010 where applicable

MOUNTING BOXES:
Min. box depth 16mm
BS 5733: 2010 where applicable

MOUNTING BOXES:
suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 2010
Refer to appropriate module for minimum box depth.
FIXING CENTRES:
1 gang: 60.3mm
2 gang: 120.6mm
BS 5733: 2010 where appropriate
Note: No grid required, modules just clip into place

Suitable for both RJ11 and RJ12 jacks.
RJ11: 4 wire
RJ12: 6 wire
MOUNTING BOXES:
Minimum box depth 35mm
FCC68
EN41003

Cat 6 performance.
Suitable for both 568A and 568B wiring schemes.
MOUNTING BOXES:
Minimum Box Depth 35mm
ISO/IEC 11801
EN 50173
TIA 568
EN 41003