

FEATURES AND BENEFITS



When servicing or repairing appliances fuse carriers on connection units can be padlocked for additional safety



A secret key-operated switch helps prevent unauthorised usage



An optional tamperproof screw on the fuse carrier is particularly useful for appliances in public areas



In-line terminals means that cables can be cut to the same length. White printing gives instant terminal identification



A simple but effective cord grip securely holds the cable in connection units



Backboxes come with or without side knockouts. All boxes have a central knockout in the base for added on-site flexibility

Socket Outlets

15 AMP
127V
SURFACE



K2271ALM



K2272ALM



K963KOALM



K942ALM



K962ALM



K962D6ALM



K3042WHI



K3062WHI

Connection Units

SWITCHED
FUSED
SURFACE

K2271ALM
1 GANG
SHUTTERED
(NON UK)

K2272ALM
2 GANG
SHUTTERED
(NON UK)

Earth terminal fitted in box.

DIMENSIONS:
1 gang 86 x 86 x 47mm
2 gang 86 x 146 x 47mm

KNOCKOUTS:
1 gang 6 x 20mm.
Two in one side and one in each of other three sides. One in base
2 gang 8 x 20mm.
Three in top, two in bottom sides and one in each end. One in base

Spare Boxes with and without knockouts are available.

All boxes have a base knockout.
SASO 2203: 2003

5 **K963KOALM**
DP WITH SECRET KEY OPERATED SWITCH, NEON AND TAMPERPROOF FUSE CARRIER SCREW

5 **K942ALM**
DP SWITCHED

K942D5ALM
DP SWITCHED WITHOUT BOX

K942KOALM
DP SWITCHED WITH TAMPERPROOF FUSE CARRIER SCREW

K962ALM
DP SWITCHED WITH NEON

K962D6ALM
DP SWITCHED WITH NEON AND RED ROCKER

All connection units are fitted with a 13A fuse (to BS 1362.)

Earth terminal fitted in base of the box.
DIMENSIONS: 86 x 86 x 47mm

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

KNOCKOUTS: 6 x 20mm.
Two in one side and one in each of other three sides, one in base.

Spare Boxes with and without knockouts are available.
All boxes have a base knockout.
BS 1363 Pt.4: 1995

1 **K3042WHI**
DP SWITCHED WITHOUT BOX

10 **K3062WHI**
DP SWITCHED WITH NEON WITHOUT BOX