

## Intelligent Dimmers (CE marked)

2 WAY SINGLE  
230V A.C. 50HZ  
60W/VA MIN.-  
500W/400VA  
MAX.

2 WAY DOUBLE  
230V A.C. 50HZ  
60W/VA MIN.  
450W/360VA  
MAX. FOR EACH  
DIMMER

2 WAY SINGLE  
230V A.C. 50HZ  
40W/VA MIN.  
300W/240VA  
MAX.

2 WAY DOUBLE  
230V A.C. 50HZ  
40W/VA MIN.  
300W/240VA MAX.  
FOR EACH DIMMER



## FINISHES

BRUSHED STAINLESS STEEL	K14301BSS	1	K14302BSS	1	K14521BSS	1	K14522BSS	1
LACQUERED BRUSHED STEEL	K14301LBS	1	K14302LBS	1	K14521LBS	1	K14522LBS	1
SILVER ANODIZED ALUMINIUM	K14301SSA	1	K14302SSA	1	K14521SAA	1	K14522SAA	1
BRUSHED CHROME	K14301BRC	1	K14302BRC	1	K14521BRC	1	K14522BRC	1
POLISHED CHROME	K14301POC	1	K14302POC	1	K14521POC	1	K14522POC	1
SATIN GOLD	K14301SAG	1	K14302SAG	1	K14521SAG	1	K14522SAG	1
PORCELAIN WHITE	K14301WHI	1	K14302WHI	1	K14521WHI	1	K14522WHI	1
TEXTURED WHITE	K14301LIV	1	K14302LIV	1	K14521LIV	1	K14522LIV	1
LUSTROUS BLACK	K14301LBK	1	K14302LBK	1	K14521LBK	1	K14522LBK	1
POLISHED BRASS	K14301PBR	1	K14302PBR	1	K14521PBR	1	K14522PBR	1
TEXTURED IRON	K14301TIR	1	K14302TIR	1	K14521TIR	1	K14522TIR	1
DESERT BRONZE	K14301DBZ	1	K14302DBZ	1	K14521DBZ	1	K14522DBZ	1
ANTIQUÉ BRASS	K14301ABS	1	K14302ABS	1	K14521ABS	1	K14522ABS	1
TEXTURED COPPER	K14301TCO	1	K14302TCO	1	K14521TCO	1	K14522TCO	1

LEAD TIMES: Please contact our Customer Services Department on: 01268 563 404

MOUNTING BOXES:  
FLUSH 866ZIC – 35mm deep min  
DIMENSIONS:  
86 x 86mm  
FIXING CENTRES: 60.3mm

MOUNTING BOXES:  
FLUSH 886ZIC – 35mm deep min  
DIMENSIONS:  
86 x 146mm  
FIXING CENTRES: 120.6mm

MOUNTING BOXES:  
FLUSH 866ZIC – 35mm deep min  
DIMENSIONS:  
86 x 86mm  
FIXING CENTRES: 60.3mm

MOUNTING BOXES:  
FLUSH 866ZIC – 35mm deep min  
DIMENSIONS:  
86 x 86mm  
FIXING CENTRES: 60.3mm

These dimmers employ the latest micro-controller based circuitry to provide electronic soft-start and overload protection. They are suitable for use with good quality electronic or wire-wound transformers. Can also be used with good quality halogen lamps incorporating GU10 bases. Please check with lamp manufacturer to determine suitability.

**NOT SUITABLE FOR FLUORESCENT LOADS.**

Conform to latest standards BS EN 60669-2-1 and BS EN 55015.

All intelligent dimmers have a combined push-on/push-off switch and rotary dimmer control, and are suitable for one or two-way switching. They are radio frequency interference suppressed to BS EN 55015.