


DATASHEET



SPKEVTMB

SpektroLED Evo Tilt - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT - Matt Black

www.mlaccessories.co.uk



| MLA PART CODE | SPKEVTMB |
|-------------------------------|---|
| DESCRIPTION | SpektroLED Evo Tilt - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT - Matt Black |
| NET WEIGHT (KG) | 0.26 |
| FINISH | Matt Black |
| DIFFUSER | Prismatic |
| DIMENSIONS (MM) | Diameter - 90 Recessed Depth - 56 Minimum Void - 56 |
| CUT-OUT (MM) | Cut-out Diameter - 70 |
| TILT (DEGREES) | 90 |
| CONSTRUCTION | Construction - Pressed steel |
| CLASS | II |
| IP RATING | IP65 (IP20 from above) |
| WATTAGE (W) | 5 / 7 |
| LAMP TECHNOLOGY | SMD LED |
| LUMENS (LM) | 565/580/605/590/745/865/825/778 |
| LUMENS LIGHT SOURCE ONLY (LM) | 1000 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 142 |
| CIRCUIT WATTAGE (W) | 7 |
| CCT | 2700/3000/4000/6000K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.037 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0.02 |
| PST-LM | 0.142 |
| BEAM ANGLE (DEGREES) | 60 |

| | |
|--|----------------------------|
| L70B10 LIFESPAN (HRS) | 50,000 |
| DIMMABLE | Yes* |
| FIRE-RATED | Tested to 30/60/90 minutes |
| I-JOIST RATED | 30 minutes |
| WEB-JOIST RATED | 30 minutes |
| IC RATED | Yes |
| ACOUSTIC RATED | Yes |
| OPERATING TEMPERATURE | 25°C |
| INPUT VOLTAGE | 230V 50Hz |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270885132 |

Date Created: 08/01/2024 21:44

