


DATASHEET



SPKEVTMB

SpektroLED Evo Tilt - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT - Matt Black

www.mlaccessories.co.uk



MLA PART CODE	SPKEVTMB
DESCRIPTION	SpektroLED Evo Tilt - Fire Rated IP65 Downlight with 2 x Wattage and 4 x CCT - Matt Black
NET WEIGHT (KG)	0.26
FINISH	Matt Black
DIFFUSER	Prismatic
DIMENSIONS (MM)	Diameter - 90 Recessed Depth - 56 Minimum Void - 56
CUT-OUT (MM)	Cut-out Diameter - 70
TILT (DEGREES)	90
CONSTRUCTION	Construction - Pressed steel
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	5 / 7
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	565/580/605/590/745/865/825/778
LUMENS LIGHT SOURCE ONLY (LM)	1000
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	142
CIRCUIT WATTAGE (W)	7
CCT	2700/3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.037
DISPLACEMENT FACTOR	>0.7
SVM	0.02
PST-LM	0.142
BEAM ANGLE (DEGREES)	60

L70B10 LIFESPAN (HRS)	50,000
DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
I-JOIST RATED	30 minutes
WEB-JOIST RATED	30 minutes
IC RATED	Yes
ACOUSTIC RATED	Yes
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270885132

Date Created: 08/01/2024 21:44

