

Item Image



## 88C 1GP

Sheer CFX Grid Bright Chrome 1 Gang Concealed Fix Grid Fix Aperture Plate with Grid.

|                               |   |
|-------------------------------|---|
| Primary Range                 | Sheer CFX   |
| Insert Type                   | GRID-IT Apertured Plates  |
| Plate Finish                  | Bright Chrome   |
| Frame Finish                  |   |
| Switch Colour                 |   |
| Body & Switch Trim            |   |
| Height                        | Single = 86mm   |
| Width                         | Single = 86mm   |
| Depth                         | Single = 4.5mm  |
| Fixing Hole Centres           | Box Fixing = 60.3mm Grid Fixing = 49.2mm<br>Box Fixing = 60.3mm Grid Fixing = 49.2mm  |
| Minimum Wall Box Depth        | 35mm  |
| Wattage                       |   |
| Switched Poles                | n/a   |
| Current Rating                |   |
| Voltage                       |   |
| Max load                      |   |
| Contact Gap Minimum           | n/a   |
| Terminal Capacity 1           |   |
| Terminal Capacity 2           |   |
| Terminal Capacity 3           |   |
| Terminal Capacity 4           |   |
| Terminal Capacity 5           |   |
| Earth Terminal Capacity 1     | 11mm <sup>2</sup>   |
| Earth Terminal Capacity 2     |   |
| Earth Terminal Capacity 3     |   |
| Earth Terminal Capacity 4     |   |
| Earth Terminal Capacity 5     |   |
| Product Class 1               | Face plate must be earthed  |
| Ambient Operating Temperature |   |
| Recommended Location          | Indoor use only   |
| Standard/Approval             |   |
| Patents and Trademarks        | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 |

|  |  |   |
|--|--|---|
| All products listed conform to current British or European standards and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.                 | It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.                  | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | Correct as at August 2012<br>E&OE   |

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK  
T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com  
www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary)  
Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire  
Registered in London No. 941624 • VAT Registration No. 222 6607 84



BS EN ISO 9001:2008  
CERT. No. FM11238

