


Item Image



88 4GP

Sheer Grid Black Nickel 4 Gang Grid Fix Aperture Plate with Grid.

Primary Range	Sheer
Insert Type	GRID-IT Apertured Plates
Plate Finish	Black Nickel
Frame Finish	
Switch Colour	
Body & Switch Trim	
Height	Double = 86mm
Width	Double = 146mm
Depth	Double = 1.5mm
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = 106.5mm Box Fixing = 120.6mm Grid Fixing = 106.5mm
Minimum Wall Box Depth	35mm
Wattage	
Switched Poles	n/a
Current Rating	
Voltage	
Max load	
Contact Gap Minimum	n/a
Terminal Capacity 1	
Terminal Capacity 2	
Terminal Capacity 3	
Terminal Capacity 4	
Terminal Capacity 5	
Earth Terminal Capacity 1	11mm ²
Earth Terminal Capacity 2	
Earth Terminal Capacity 3	
Earth Terminal Capacity 4	
Earth Terminal Capacity 5	
Product Class 1	Face plate must be earthed
Ambient Operating Temperature	
Recommended Location	Indoor use only
Standard/Approval	
Patents and Trademarks	Trade Mark No. 2296586

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.

Correct as at August 2012
E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK
T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com
www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary)
Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire
Registered in London No. 941624 • VAT Registration No. 222 6607 84



BS EN ISO 9001:2008
CERT. No. FM11238

