

www.hamilton-litestat.com

Item Image (6) Wiring **Dimensions** SHEER SHAVER SOCKET (Dual Voltage) Hamilton

81 SHS B

Sheer Polished Brass Shaver Socket Dual Voltage. Standard Insert will be Black.

Primary Range Sheer Insert Type Shaver Sockets Plate Finish Polished Brass Frame Finish Switch Colour Body & Switch Trim Black Height Double Vertically Mounted = 146mm Width Double Vertically Mounted = 86mm Depth Double Vertically Mounted = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm VerticalBox Fixing = 120.6mm Vertical Minimum Wall Box Depth 47mm Wattage Switched Poles none Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 2 x 4mm2 Multi-Strand Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 2 x 4mm2 Multi-Strand Earth Terminal Capacity 9 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating -5° to +40°C Recommended Location Indoor use only Standard/Approval 85 EN 61558 - BS 4573			
Plate Finish Frame Finish Switch Colour Body & Switch Trim Height Double Vertically Mounted = 146mm Width Double Vertically Mounted = 86mm Depth Double Vertically Mounted = 1.5mm Fixing Hole Centres Minimum Wall Box Depth Wattage Switched Poles Current Rating Voltage Voltage Voltage Voltage Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Term			
Frame Finish Switch Colour Body & Switch Trim Height Double Vertically Mounted = 146mm Double Vertically Mounted = 86mm Double Vertically Mounted = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm VerticalBox Fixing = 120.6mm Vertical Minimum Wall Box Depth Wattage Switched Poles Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Sanda Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth			
Switch Colour Body & Switch Trim	. 1215	Polished Brass	
Body & Switch Trim Height Double Vertically Mounted = 146mm Width Double Vertically Mounted = 86mm Double Vertically Mounted = 1.5mm Fixing Hole Centres Minimum Wall Box Depth Wattage Switched Poles Current Rating Voltage Voltage Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 9 Terminal Capacity 9 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 9 Terminal Capaci			
Height Double Vertically Mounted = 146mm Width Double Vertically Mounted = 86mm Depth Box Fixing = 120.6mm VerticalBox Fixing = 120.6mm Vertical Wattage Switched Poles none Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 7 1 x 6mm2 Earth Terminal Capacity 8 2 x 4mm2 Multi-Strand Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 1 5 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating 7-5° to +40°C Recommended Location Indoor use only	0.1.11		
Width Depth Double Vertically Mounted = 86mm Depth Fixing Hole Centres Minimum Wall Box Depth Wattage Switched Poles Current Rating Voltage Voltage Terminal Capacity 1 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 1 Terminal Capacity 1 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacit	Body & Switch Trim	Statit	
Double Vertically Mounted = 1.5mm	Height	Double Vertically Mounted = 146mm	
Fixing Hole Centres Box Fixing = 120.6mm VerticalBox Fixing = 120.6mm Vertical Minimum Wall Box Depth Wattage Switched Poles Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 9 E	Width		
Minimum Wall Box Depth 47mm Wattage Switched Poles none Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 6 x 1.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Depth	Double Vertically Mounted = 1.5mm	
Wattage Switched Poles none Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 5 1 x 6mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 7 5 x 4 x 2.5mm2 Earth Terminal Capacity 8 5 x 4 x 2.5mm2 Earth Terminal Capacity 9 x 1 x 6mm2 Earth Terminal Capacity 9 x 1 x 6mm2 Product Class 1 Aust be earthed Ambient Operating Temperature Recommended Location Indoor use only		Box Fixing = 120.6mm VerticalBox Fixing = 120.6mm Vertical	
Switched Poles none Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 6 x 1.5mm2 Earth Terminal Capacity 6 x 2.5mm2 Earth Terminal Capacity 7 2 x 4mm2 Multi-Strand Earth Terminal Capacity 8 4 x 2.5mm2 Earth Terminal Capacity 9 x 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating 7 to +40 °C Recommended Location Indoor use only	Minimum Wall Box Depth	47mm	
Current Rating 20VA Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5x 1mm2 Terminal Capacity 2 4x 1.5mm2 Terminal Capacity 3 3x 2.5mm2 Terminal Capacity 4 2x 4mm2 Multi-Strand Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 1 9x 1mm2 Earth Terminal Capacity 2 6x 1.5mm2 Earth Terminal Capacity 3 1x 6mm2 Earth Terminal Capacity 4 2x 4mm2 Multi-Strand Earth Terminal Capacity 5 1x 6mm2 Earth Terminal Capacity 5 1x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	. 3		
Voltage 220/250V AC Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Switched Poles	none	
Max load 200/250V input; 115/230V 20VA output Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Current Rating	2017.	
Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Voltage	220/250V AC	
Contact Gap Minimum n/a Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Max load	200/250V input; 115/230V 20VA output	
Terminal Capacity 2	Contact Gap Minimum	n/a	
Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 4 2 x 4mm2 Multi-Strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 5	Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40° C Recommended Location Indoor use only	Terminal Capacity 4	2 x 4mm2 Multi-Strand	
Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Indoor use only	Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Indoor use only	Earth Terminal Capacity 1	9 x 1mm2	
Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Indoor use only	Earth Terminal Capacity 2	6 x 1.5mm2	
Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Indoor use only	Earth Terminal Capacity 3	4 x 2.5mm2	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Indoor use only		2 x 4mm2 Multi-Strand	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Indoor use only	Earth Terminal Capacity 5	1 x 6mm2	
Temperature -5 to +40 C Recommended Location Indoor use only		Must be earthed	
Temperature Endowment Recommended Location Indoor use only	Ambient Operating	E° to .40°C	
, , , , , , ,	Temperature	-5 t0 +40 C	
Standard/Approval BS EN 61558 - BS 4573	Recommended Location	Indoor use only	
	Standard/Approval	BS EN 61558 - BS 4573	
Patents and Trademarks Trade Mark No. 2296586	Patents and Trademarks	Trade Mark No. 2296586	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84







