

MIRAS TOUCH



Touchscreen Chronothermostats

- Touchscreen, 7 easy to configure programs
- Easy and intuitive programming with copy/paste function
- Large backlit display for easy reading
- Three adjustable temperature levels, manual mode and temporary manual

THALOS



Touchscreen Thermostat

- Touchscreen • Easy and intuitive programming
- Large backlit display for easy reading
- Input for night temperature reduction
- Has 3 temperature settings plus anti-icing to avoid frozen pipes

VELUS TOUCH



Touchscreen Thermostat

- Touchscreen, Large backlit display for easy reading
- Adjustable temperature values for Summer/Winter modes
- Each mode includes three temperature configurations (Comfort, Economy or Anti-freeze)
- Manual regulation operation or standby

DRT1



Digital Room Thermostat, 5A

- Easy to use digital thermostat (24hr). Battery operated,
- Flush or surface mounted, accurate temperature control (0.5°C)
- Function displays symbols to indicate on/off status
- Fits directly onto 1 gang flush box (35mm)
- Heating or cooling operation. 2 core cable. 5A contact rating
- Battery operated (2x AAA not supplied)

DRT2



Digital Room Thermostat, Programmable (24Hr, 7 Day), 5A

- 4 in-built programmes per time group, e.g (weekdays-Saturday or Sunday)
- Battery operated. Flush or surface mounted
- Accurate temperature control (0.5°C)
- Function displays symbols to indicate on/off status
- Temporary or permanent override
- 12/24hr clock display time adjustable in 15 minute segments

DRT1RC



Digital Room Thermostat, Radio Controlled, Wire-Free, 5A

- 24hr, 7 day programmable with 4 in-built programmes per time group, e.g (weekdays-Saturday or Sunday)
- Battery operated sensor
- Flush or surface mounted
- Pre wired, mains operated receiver (surface mounted)
- Accurate temperature control (0.5°C)

DRT2RC



Digital Room Thermostat, Programmable, Radio Controlled, Wire-Free, 5A

- 24hr, 7 day programmable with 4 in-built programmes per time group, e.g (weekdays-Saturday or Sunday)
- Battery operated sensor • Flush or surface mounted
- Pre wired, mains operated receiver (surface mounted)
- Accurate temperature control (0.5°C)

RT16/2



Room Thermostat, 16A

- Small, precision ambient thermostat with a compact design
- No power supply needed, allows blocking of temperature to avoid changes
- 2 wire compact thermostat. High amperage contacts
- Suitable for heating or cooling

RT16/3



Room Thermostat, 16A

- Small, precision ambient thermostat with a compact design
- No power supply needed, allows blocking of temperature to avoid changes
- 3 wire compact thermostat. High amperage contacts
- Suitable for heating or cooling

RT16/3N



Room Thermostat with Neon Indicator Light

- 3 wire thermostat with an accelerator, fast response operation
- Room temperature control of heating, cooling or fan devices
- Power supply: 230V AC • Temperature range: 10°C to 30°C
- Current rating – heating: 16A (4)
- Cable requirements: 3 core

FTR/N



10A Froststat

- Control of low temperature switching in internal applications • Accelerator fitted for fast response • 10A contact rating
- Minus 5 to 15°C temperature range • Suitable for garages and other internal applications
- 3 wire thermostat with high amperage contacts
- Can also be used for ventilation control