

1

SEA91253N



SEA9NI2504



SEA9R14463



SEA9TB1254



SEA9BNDM250SD



Int= Internal to the distribution board  
Ext = in 400mm high extension enclosures  
■ = not applicable

Incomers							
Switch disconnecter	Rating (A)	No of poles	Standard	Meter ready	Split Metered	IP55	
SEA91253N	125	3P+N	Int	Int	Int	Int	
SEA91254	125	4	Int	Int	Int	Int	
SEA9NI1603	160	3P+N	Ext	Ext	Ext	■	
SEA9NI1604	160	4	Ext	Ext	Ext	■	
SEA9NI2003	200	3P+N	Ext	Ext	Ext	■	
SEA9NI2004	200	4	Ext	Ext	Ext	■	
SEA9NI2254	225	4	Ext	Ext	Ext	■	
SEA9NI2503	250	3P+N	Ext	Ext	Ext	■	
SEA9NI2504	250	4	Ext	Ext	Ext	n ■	
Moulded Case Circuit Breaker	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
SEA9NCB1004	70-100	4	Ext	Ext	Ext	■	
SEA9NCB1604	112-160	4	Ext	Ext	Ext	■	
SEA9NCB2004	140-200	4	Ext	Ext	Ext	■	
SEA9NCB2504	175-250	4	Ext	Ext	Ext	■	
Residual current circuit breaker sensitivity (mA)	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
A9R41463	30	63	4	Int	Int	Int	
A9R12463	100	63	4	Int	Int	Int	
A9R44463	300	63	4	Int	Int	Int	
A9R15463	300/time delayed	63	4	Int	Int	Int	
A9R11480	30	80	4	Int	Int	Int	
A9R14491	300	100	4	Int	Int	Int	
A9R15491	300/time delayed	100	4	Int	Int	Int	
SEA9NI160RCCB	adjustable	160	■	Ext	Ext	Ext	
Terminals for direct connection	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
SEA9TB1254	125	4	Int	Int	Int	Int	
SEA9NTB2504	250	4	Ext	Ext	Ext	■	
Dual source incomer	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
SEA9NDSI	*270mm enclosure	125	4	Ext	Ext	Ext	
Contactormeter incomer	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
SEA9BN100CCI	*270mm enclosure	100	4	Ext	Ext	Ext	
Dual metered extension enclosure MID 3 Phase kWh kit Modbus communications and pulsed output 270mm enclosures	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
SEA9BNDM160SD	Interpact SD	160	4	Ext 270mm	■	■	
SEA9BNDM200SD	Interpact SD	200	4	Ext 270mm	■	■	
SEA9BNDM250SD	Interpact SD	250	4	Ext 270mm	■	■	
SEA9BNDM160M	NSX MCCB	160	4	Ext 270mm	■	■	
SEA9BNDM200M	NSX MCCB	200	4	Ext 270mm	■	■	
SEA9BNDM250M	NSX MCCB	250	4	Ext 270mm	■	■	
Single phasing kits	Rating (A)	No of poles	Standard	Meter ready	Split metered	IP55	
SEA9125SPEV	125	4	Int	Int	Int	Int	
SEA9250SPEV	250	4	Int	Int	Int	■	