

1

Weight (kG) - Dimensions (mm)								
Standard	Multi service	Split load	Dual Incomer	Split metered	kG	Height	Width	Depth
2 way	■	■	■	■	1.8	300	200	117
6 way	■	■	■	■	2.5	300	273	117
10 way	■	■	2 - 6	■	3.0	300	345	117
14 way	6 - 16, 10 - 8	5 - 6	6 - 6	■	4.8	300	417	117
18 way	6 - 24, 10 - 16, 14 - 8	5 - 10, 9 - 6	10 - 6	6 - 6	5.7	300	489	117
27 way	14 - 32	10 - 10, 14 - 14	■	10 - 10	8.9	530	417	117



Incomers			
Switch disconnecter		Rating (A)	No of poles
SEA91252		125	2
Residual current circuit breaker 230/240vAC		Rating (A)	No of poles
Sensitivity (mA)			
SEA9R41263	30	63	2
SEA9R12263	100	63	2
SEA9R44263	300	63	2
SEA9R11280	30	80	2
SEA9R12280	100	80	2
SEA9R14280	300	80	2
SEA9R15280	300 TD	80	2
SEA9R11291	30	100	2
SEA9R12291	100	100	2
SEA9R14291	300	100	2
SEA9R15291	300 TD	100	2
Terminal block		Rating (A)	No of poles
SEA9TB1252		125	2

DIN rail only enclosures			
Reference	Description	Number of rows	Dimensions as
SEA9DE16	8 SP way module enclosure	1	SEA9AN6
SEA9DE24	12 SP way module enclosure	1	SEA9AN10
SEA9DE32	16 SP way module enclosure	1	SEA9AN14
SEA9DE40	20 SP way module enclosure	1	SEA9AN18
SEA9DE64	32 SP way module enclosure	2	SEA9AN27