



CMA140, CMA145



CMA146



CMA161



CMA162



CMA147



CMA148



CMA163



CMA164

**MINIGRID®**

Interchangeable modules available on page J37.

**Dimmer Switches (Leading Edge)**

- CMA140 1 Gang 2 Way 400Va Dimmer Switch
- CMA145 1 Gang 2 Way 250Va Dimmer Switch
- CMA146 2 Gang 2 Way 250Va Dimmer Switch
- CMA147 3 Gang 2 Way 250Va Dimmer Switch
- CMA148 4 Gang 2 Way 250Va Dimmer Switch

We recommend the use of branded halogen lamps with all Mode® leading edge dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. These dimmer switches have not been designed for use with LED lamps. However, they may be suitable for some good quality LED lamps. For further information please contact the Click® Technical support team.

Standards: BS EN 60669-1 BS EN 55015 BS EN 61000-3-2 BS EN 61000-3-3  
 Back Box Depth: 25mm Minimum  
 Cable Size: 2 x 1.5mm<sup>2</sup>  
 Type: Leading Edge  
 Dimensions: 1 Gang: 86mm (W) x 86mm (H) x 9.5mm (D) 2 Gang: 146mm x 88mm x 8mm

**MINIGRID®**

Interchangeable modules available on page J37.

**Dimmer Switches (Trailing Edge)**

- CMA161 1 Gang 2 Way 100W Dimmer Switch
- CMA162 2 Gang 2 Way 100W Dimmer Switch
- CMA163 3 Gang 2 Way 100W Dimmer Switch
- CMA164 4 Gang 2 Way 100W Dimmer Switch

We recommend the use of branded LED lamps with all Mode® trailing edge dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team.

Standards: BS EN 60669-1 BS EN 60669-2-1 BS EN 55015 BS EN 61000-3-2  
 Type: Trailing Edge  
 Back Box Depth: 25mm Minimum  
 Cable Size: 2 x 1.5mm<sup>2</sup>  
 Dimensions: 1 Gang: 86mm (W) x 86mm (H) x 9.5mm (D) 2 Gang: 146mm (W) x 86mm (H) x 9.5mm (D)