

Kraftform Kompakt VDE 15 Torque 1.2-3.0 Nm extra slim 1, 15 pieces

Series 7400 Insulated Kraftform Torque Screwdrivers



EAN:	4013288168375	Size:	225x150x80 mm
Part number:	05059291001	Weight:	760 g
Article number:	Kraftform Kompakt VDE 15 Torque 1,2-3,0 Nm extra slim 1	Country of origin:	CZ
		Customs tariff number:	82054000

- Kraftform Kompakt VDE torque screwdriver set with adjustable torque
- Adjustable Kraftform VDE torque holder exclusively for Wera VDE interchangeable blades
- VDE interchangeable blades 154 mm long
- In robust pouch
- 15-piece

15-piece torque VDE interchangeable blade set. Includes 14 blades (12 of which with a reduced diameter) with integrated insulation protection. Torque VDE holder with adjustable torque from 1.2-3.0 Nm. Kraftform Plus handle: hard gripping zones for high working speeds whereas soft zones ensure high torque transfer.



Web link

https://products.wera.de/en/tools_for_electricians_insulated_torque_tools_series_7400_insulated_kraftform_torque_screwdrivers_kraftform_kompakt_vde_15_torque_1_2-3_0

Wera - Kraftform Kompakt VDE 15 Torque 1,2-3,0 Nm extra slim 1
05059291001 - 4013288168375









Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Kraftform Kompakt VDE 15 Torque 1.2-3.0 Nm extra slim 1, 15 pieces



Series 7400 Insulated Kraftform Torque Screwdrivers


Set contents:

	7400 VDE 05074750001 1 x 7441 VDE x 1.2-3.0 Nm		KK 62 iS 05003413001 1 x PH 1 x 154 mm 05003414001 1 x PH 2 x 154 mm
	KK 65 iS PZ 05003455001 1 x PZ 1 x 154 mm 05003456001 1 x PZ 2 x 154 mm		KK 65 iS PZ/S 05003447001 1 x # 1 x 154 mm 05003448001 1 x # 2 x 154 mm
	KK 67 i TORX® 05003431001 1 x TX 10 x 154 mm		KK 67 iS TORX® 05003437001 1 x TX 15 x 154 mm 05003438001 1 x TX 20 x 154 mm 05003439001 1 x TX 25 x 154 mm
	KK 60 i 05003400001 1 x 0.4 x 2.5 x 154 mm		KK 60 iS 05003406001 1 x 0.6 x 3.5 x 154 mm 05003407001 1 x 0.8 x 4 x 154 mm 05003408001 1 x 1 x 5.5 x 154 mm

Individually tested




Kraftform adjustable torque handle for Electricians



Each Kraftform Kompakt VDE set has been tested individually at 10,000 volts, in accordance with IEC 60900. This ten-times-higher testing load guarantees safe working at their maximum permitted load of 1,000 volts.

Handle/interchangeable blade system – Kraftform Kompakt VDE



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.

Kraftform adjustable torque handle for Electricians



Easy-to-read scale value. Measurement accuracy is $\pm 6\%$ in accordance with the standard EN ISO 6789.

Web link

https://products.wera.de/en/tools_for_electricians_insulated_torque_tools_series_7400_insulated_kraftform_torque_screwdrivers_kraftform_kompakt_vde_15_torque_1_2-3_0

Wera - Kraftform Kompakt VDE 15 Torque 1,2-3,0 Nm extra slim 1
05059291001 - 4013288168375

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Kraftform adjustable torque handle for Electricians




Simple setting of the required torque by hand.

Excess-load signal




Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Inserting the blade



According to the job, the insulated inter-changeable blade with the required tipstyle, or a switch cabinet key is inserted into the clamping mechanism.

Taking out the blade



By pulling and holding down the clamping sleeve the interchangeable screwdriver blade, or the switch cabinet key, is unlocked and can easily be taken out of the handle.

Web link

https://products.wera.de/en/tools_for_electricians_insulated_torque_tools_series_7400_insulated_kraftform_torque_screwdrivers_kraftform_kompakt_vde_15_torque_1_2-3_0

Wera - Kraftform Kompakt VDE 15 Torque 1,2-3,0 Nm extra slim 1
05059291001 - 4013288168375

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de