

Product datasheet

Specifications



TeSys F - contactor coil - LX1FH - 380...415 V AC 40...400 Hz

Local distributor code: 380914094 LX1FH3802

! Discontinued on: 31 December 2022

EAN Code : 3389110553376

! To be discontinued

Main

| | |
|------------------------------|--|
| Range | TeSys |
| Product or component type | Contactor coil |
| Device short name | LX1FH |
| Range compatibility | TeSys (TeSys F) LC1F contactor |
| Product compatibility | LC1F330 LC1F265 |
| Control circuit type | AC at 40...400 Hz |
| [Uc] control circuit voltage | 380...415 V AC 40...400 Hz |
| Average resistance | 217 Ohm inrush at 20 °C 4631 Ohm holding at 20 °C |
| Operating time | 100...170 ms opening 40...65 ms closing |
| Mechanical durability | 10 Mcycles |
| Maximum operating rate | 2400 cyc/h 55 °C |

Complementary

| | |
|---------------------------------|--|
| Coil technology | Without built-in suppressor module |
| Control circuit voltage limits | Drop-out: 0.35...0.55 Uc 40...400 Hz (at 55 °C) Operational: 0.85...1.1 Uc 40...400 Hz (at 55 °C) |
| Inrush power in VA | 650 VA 40...400 Hz cos phi 0.9 (at 20 °C) |
| Hold-in power consumption in VA | 10 VA 40...400 Hz cos phi 0.3 (at 20 °C) |
| Heat dissipation | 8 W at 40...400 Hz |

Environment

| | |
|---------------------------------------|------------|
| Ambient air temperature for operation | -5...55 °C |
| Net weight | 0.75 kg |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

| | |
|------------------------------|-----------|
| Package 1 Height | 18.54 cm |
| Package 1 Width | 10.16 cm |
| Package 1 Length | 9.14 cm |
| Package 1 Weight | 0.85 kg |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 30 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 10.526 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)