

3 Year Warranty

L70 25,000hrs

Triac dimmable as standard


White, Matt White, Polished Chrome & Satin Nickel bezel finish options





Triac Inline Dimmer See pg.41



Smart Rotary Dimmer See pg.35



AU-A4



AU-A4

(H) 69mm Height (OD) 78mm Overall (Ø)

AU-A42

(H) 90mm Height (OD) 88mm Overall (Ø)

A4™

LED Fixed/Adjustable Fire Rated Downlights

make smart with



See pg.256-258 for compatibility table

Delivering up to 105lm/W

Hinged cap and latching terminals for faster installation

Slim, interchangeable IP65 bezels (fixed version) providing a sleek finish

IP20 bezel included for adjustable version

60° beam angle for uniform light distribution

Fibre based insulation coverable - up to 300mm

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings†



Fixed IP65



Adjustable

Fire Rated Downlights



Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cutout [Ø]
A4™ Triac Dimmable Fixed (IP65 when used with IP65 Bezel)						
AU-A4/30	4W	3000K	400lm	100	60°	65mm
AU-A4/40	4W	4000K	410lm	103	60°	65mm
A4™ Triac Dimmable Adjustable						
AU-A42*/30	4W	3000K	410lm	103	60°	75mm
AU-A42*/40	4W	4000K	420lm	105	60°	75mm

Bezel Options

A4™ Fixed IP65 Aluminium Downlight Bezel

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.

†Suitable for use in 30 minute i-joist fire rated ceilings. See pg.262

