



MR16/MR11, 12V & 240V LED Lamps

- Multi faceted reflector lens that mimics halogen MR16
- Effective heat management technology
- Delivering up to 104lm/W
- 60° beam angle for maximum light distribution
- 38° beam angle available for focused spotlighting

make smart with



See pg.256-258 for compatibility table

3 Year Warranty

L70 25,000hrs



works with

.control




On/Off Relay
See pg.47



12V MR16


240V GU10

12V MR11



| Cat. No. | Base | Watts | Colour | Lumens | lm/W | Beam |
|-------------------------------|-------|-------|--------|--------|------|------|
| Non-Dimmable 12V MR16 | | | | | | |
| EN-MR165/30 | GU5.3 | 5W | 3000K | 500lm | 100 | 60° |
| EN-MR165/40 | GU5.3 | 5W | 4000K | 520lm | 104 | 60° |
| EN-MR1653/30 | GU5.3 | 5W | 3000K | 500lm | 100 | 38° |
| EN-MR1653/40 | GU5.3 | 5W | 4000K | 520lm | 104 | 38° |
| Non-Dimmable MR11 GU10 | | | | | | |
| EN-MR11GU4/30 | GU10 | 4W | 3000K | 290lm | 73 | 60° |
| EN-MR11GU4/40 | GU10 | 4W | 4000K | 300lm | 75 | 60° |
| Non-Dimmable 12V MR11 | | | | | | |
| EN-MR1116/30 | GU4.0 | 1.6W | 3000K | 160lm | 100 | 60° |
| EN-MR1116/40 | GU4.0 | 1.6W | 4000K | 160lm | 100 | 60° |

For 12V lamp - requires AU-LED1012CV (one lamp per driver)



EN-MR165

(L) 51mm Length
(OD) 50mm Overall (Ø)

EN-MR1653

(L) 51mm Length
(OD) 50mm Overall (Ø)

EN-MR1116

(L) 35mm Length
(OD) 35mm Overall (Ø)

EN-MR11GU4

(L) 48mm Length
(OD) 34mm Overall (Ø)