

3 Year Warranty

L70 35,000hrs

White finish



On/Off Relay
See pg.47



EcoT8™

Single & Twin Slimline Battens

make smart with



See pg.256-258 for compatibility table

Steel housing and high quality polycarbonate diffuser eliminates hot spots providing uniformed low glare light output


Delivering up to 97lm/W

Perfect for retrofitting existing installations or as an alternative to T8 or T5 fluorescent fittings


Easy access rear terminal block

Integrated driver supplied in housing

EN-BT1218



EN-BT1233




Linears



Single



Twin



All products - Height 35mm

EN-BT1218 (L) 1220mm Length (W) 55mm Width	EN-BT1233 (L) 1220mm Length (W) 85mm Width
EN-BT1522 (L) 1520mm Length (W) 55mm Width	EN-BT1544 (L) 1520mm Length (W) 85mm Width
EN-BT1827 (L) 1820mm Length (W) 55mm Width	EN-BT1851 (L) 1820mm Length (W) 85mm Width

Cat. No. Type Watts Colour Lumens lm/W Length (ft)

Single

EN-BT1218/40	Non-Dim	18W	4000K	1600lm	89	4
EN-BT1522/40	Non-Dim	22W	4000K	2100lm	95	5
EN-BT1827/40	Non-Dim	27W	4000K	2500lm	93	6

Twin

EN-BT1233/40	Non-Dim	33W	4000K	3200lm	97	4
EN-BT1544/40	Non-Dim	44W	4000K	4100lm	93	5
EN-BT1851/40	Non-Dim	51W	4000K	4500lm	88	6

