

QuaZar™

IP65 HV Driverless Floodlights

make smart with

 See pg.256-258 for compatibility table



3 Year Warranty
 L70 25,000hrs
 Black or White finish options

- Slim design
- Aluminium housing with tempered glass lens
- Delivering up to 100lm/W
- IP65 rated
- IK08 rated impact resistance
- Pre-wired with 800mm of cable

make smart with


works with


 On/Off Relay
 See pg.47



EN-FLH10
 (H) 93mm Height
 (W) 121mm Width
 (D) 24mm Depth
 (BL) 80mm Bracket Length
 (BW) 134mm Bracket Width

EN-FLH20
 (H) 127mm Height
 (W) 167mm Width
 (D) 26mm Depth
 (BL) 100mm Bracket Length
 (BW) 174mm Bracket Width

EN-FLH30
 (H) 155mm Height
 (W) 200mm Width
 (D) 26mm Depth
 (BL) 115mm Bracket Length
 (BW) 205mm Bracket Width

EN-FLH50
 (H) 175mm Height
 (W) 225mm Width
 (D) 30mm Depth
 (BL) 130mm Bracket Length
 (BW) 231mm Bracket Width

Cat. No.	Watts	Colour	Lumens	lm/W
Non-Dimmable				
EN-FLH10*/30	10W	3000K	900lm	90
EN-FLH10*/40	10W	4000K	900lm	90
EN-FLH20*/30	20W	3000K	1800lm	90
EN-FLH20*/40	20W	4000K	1800lm	90
EN-FLH30*/30	30W	3000K	2700lm	90
EN-FLH30*/40	30W	4000K	2700lm	90
EN-FLH50*/30	50W	3000K	5000lm	100
EN-FLH50*/40	50W	4000K	5000lm	100

*Add suffix **W** or **BLK** for White or Black finish



Floodlights