M-Lite™PRO

IP68 LED Marker Lights

make smart with
Aone control

See pg.256-258 for compatibility table

316 stainless steel

IP68 rated

Pre-wired with 3 metres of rubber cable, (1 metre rubber cable EN-WU104)

Optional mounting sleeves available (sold separately) EN-MS50 for EN-WU106, EN-MS65 for EN-WU300

make smart with
Aone control

works with

.control

On/Off Relay
See pg.47   ▲ 16 A

| EN-WU104 | EN-WU105 | EN-WU106 | EN-WU300 |

| EN-MS50 | EN-MS65 | 350mA see pg.246 | 24V see pg.243 |

Marker Lights

EN-WU104
(OD) 40mm Overall Ø
(H)   50mm Height

EN-WU105
(OD) 36mm Overall Ø
(H)   50mm Height

EN-WU106
(OD) 60mm Overall Ø
(H)   60mm Height

EN-WU300
(OD) 76mm Overall Ø
(H)   60mm Height

Cat. No.	Watts	No. of LEDs	Colour	Lumens	No. of Fittings per driver		Cutout [Ø]	Input
					AU-LED09IP	AU-LED1624IP		
EN-WU104/30	1W	1	3000K	100lm	1-5	-	32mm	350mA
EN-WU105/30	1W	1	3000K	50lm	-	10	27mm	24V
EN-WU106/30	1W	1	3000K	100lm	1-5	-	50mm	350mA
EN-WU300/30	3W	3	3000K	190lm	1-3	-	65mm	350mA

Accessories

| EN-MS50 | Mounting sleeve for EN-WU106 |
| EN-MS65 | Mounting sleeve for EN-WU300 |

CRI 80 | III | IP68 | L1 Conservation of Fuel and Power exempt

Exempt