

Technical Specification



Product Code: VPCH551BK Description: 13A Ingot Double Pole Switched Fused Connection Unit With Optional Flex

Dutlet





Representative Image

General Information

Plate Design & Finish Victorian Polished Chrome

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert & Housing: Urea

Switch & Fuse Drawer Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 13A
Plate Fixing Centres 60.3mm
Terminal Size 5mmø

Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

Switched Yes
Double Pole Yes
Twin Earth Terminals Yes

Fuse Fitted 13A (BS 1362)

Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-4: 2016 +A1: 2018

BS 1362:1973

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.