essentials[™]

Technical Specification

Product Code: WA179 Description: 13A 2 Gang Unswitched Socket Outlet





Representative Image

General Information

Dimensions 146mm (W) x 86mm (H) x 11mm (D)

Finish Red

Materials Front Plate: Urea

Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A

Plate Fixing Centres 120.6mm
Terminal Size 5mmø

Terminal Torque 2.5Nm
Terminal Capacity 4 x 2.5mm²

Switched No

Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All urea moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.

All products have been independently tested and achieved a 99.9% kill rate across all four types of

the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

