

E6TM PRO

LED Fixed/Adjustable Fire Rated Downlights

make smart with



See pg.256-258 for compatibility table

- Sparkling, low glare, multifaceted EnFinitiTM lens
- Delivering up to 117lm/W
- Slim, interchangeable IP65 bezels (fixed version) provide a sleek finish
- IP20 bezel included for adjustable
- Unique RapidWire connection system
- Removable connector allows full circuit insulation resistance testing
- Fibre based insulation coverable - up to 300mm
- 60° beam angle for uniform light distribution
- Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings†



Fixed IP65

Adjustable



AIR leakage (excluding adjustable)

Cat. No. Watts Colour Lumens lm/W Beam Cutout [Ø]

E6TMPRO Triac Dimmable Fixed (IP65 when used with IP65 Bezel)

EN-DE6PRO [†] /30	6W	3000K	580lm	97	60°	70mm
EN-DE6PRO [†] /40	6W	4000K	620lm	103	60°	70mm

E6TMPRO Triac Dimmable Adjustable

EN-DE62PRO [*] /30	6W	3000K	680lm	113	60°	80mm
EN-DE62PRO [*] /40	6W	4000K	700lm	117	60°	80mm

Accessories

EN-BZE8* E6TM PRO/E8TM Fixed IP65 Aluminium Downlight Bezel

NEW AU-AP86* Fire Rated Aluminium Adaptor Plate Fixed 85-145mm

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.

†Add suffix **EM** for Emergency

†Suitable for use in 30 minute i-joist fire rated ceilings. See pg.262



DE6PRO DE62PRO

5 Year Warranty

L70 50,000hrs

Triac dimmable as standard

Emergency option


White, Matt White, Polished Chrome & Satin Nickel bezel finish options

make smart with



works with

.control





Smart Rotary Dimmer
See pg.35



Triac Inline Dimmer
See pg.41

EN-DE6PRO



EN-DE6PRO

(H) 100mm Height
(OD) 85mm Overall (Ø)

EN-DE62PRO

(H) 105mm Height
(OD) 95mm Overall (Ø)