

3 Year Warranty


White or Matt White
bezel finish options



works with


.light

Smart
Tuneable GU10
See pg.27




.control



Dimmable
Standard GU10
PLUS
Triac Inline Dimmer
See pg.41



OR
Smart Rotary Dimmer
See pg.35



Non-Dimmable
Standard GU10
PLUS
On/Off Relay
See pg.47



EN-DLM482
(H) 135mm Height
(OD) 95mm (Ø) Enc.

EN-DLM484
(H) 130mm Height
(OD) 95mm Overall (Ø)

EFD™

GU10 Baffled Fire Rated Downlights

make smart with



See pg.256-258 for compatibility table

- Pressed steel body with aluminium bezel
- Black baffle designed to reduce direct glare
- Lock ring for ease of lamp replacement
- EN-DLM482 - Adjustable up to 20° and IP20 rated
- EN-DLM484 - IP44 rated

Fibre based insulation coverable - up to 300mm when used with insulation cap (included)

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings

Smart
Lamp options
See pg.27



Standard
Lamp options
See pg.113



See luminaire lamp compatibility on pg.259



Adjustable Baffle



Fixed Baffle IP44



AIR leakage
(excluding
adjustable)

Cat. No.	Input	Horz. Adj.	Cutout (Ø)
Adjustable Baffle			
EN-DLM482*	240V	20°	80mm
IP44 Fixed Baffle			
EN-DLM484*	240V	-	80mm

*Add suffix **WB** or **MWB** for White Baffle or Matt White Baffle finishes.
Lamp not included



Fire Rated Downlights