

3 Year Warranty

L70 35,000hrs

3000K, 4000K, 6300K &
Blue colour options



works with

.control

12/24V Inline Controller
see pg.43

▲ 12/24

On/Off Relay
see pg.47

▲ 16A




EN-STIPCK

IP Rated Kit Includes

- 2 power leads
- 2 end caps
- 4 heat shrink sleeves
- 1 tube of sealant
- 6 fixing clips
- 12 fixing screws

Requires soldering



LEDlineTM PRO

12V IP67 LED Strip

make smart with



See pg.256-258 for compatibility table

Single colour flexible IP67 LED strip with 3MTM self adhesive backing

Cut points every 50mm for maximum flexibility

Beam angle of 120° and 17mm between LEDs, 60 LEDs per metre

Voltage drop of 4V per 10m and maximum run of 10m

Any joints or termination points are maximum IP65 rated

For runs over 10m individual lengths should be connected in parallel

Reel length 10m



Cat. No.	Watts/m	No. of LEDs/m	Colour	lm/m
EN-ST100IP/30	4.8W	60	3500K	475lm
EN-ST100IP/40	4.8W	60	4000K	494lm
EN-ST100IP/60	4.8W	60	6300K	518lm
EN-ST100IP/BLU	4.8W	60	Blue	-

Accessories

[EN-STIPCK](#) LEDLineTM PRO IP67 Strip Connector Kit

Cat. No.	Description	Metres per driver
LED Drivers		
AU-LED1012CV	10W Non-Dimmable 12V Constant Voltage Driver	1m
AU-LED2512CV	25W Non-Dimmable 12V Constant Voltage Driver	5m
EN-LED7512	75W Non-Dimmable 12V Constant Voltage Driver	10m
EN-LEDD7512	75W Triac Dimmable 12V Constant Voltage Driver	10m

For alternative lengths see pg.245



Strip