

**Product Code:** ZPBF1L

**Description:** ZWALUW Instant Plaster Filler Tub - White



**Benefits**

- Ultra lightweight
- Almost non-shrinking
  - Paintable with water based- and synthetic paints
  - Sandable after curing
  - Easy to apply
  - Easy to clean
  - Non corrosive towards metals

Zwaluw Plasterboard-Filler is virtually a non shrinking, ready to use ultra light, ready mixed filler and spackling compound for filling and repairing cracks and holes in walls and ceilings.

**Colour:** White

**Applications**

Zwaluw Plasterboard-Filler was specifically developed for filling one time joints and screw holes in plasterboard walls and ceilings for interior applications. Also for one time filling, repairing and smoothing of holes and cracks in concrete, plaster, brickwork and stucco layers.

**Directions Of Use**

For best results, the product should be applied without pressure.

**Limitations**

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates
- Not suitable for continuous exposure to water
- Not suitable for movement joints

**Paintability**

Zwaluw Plasterboard-Filler is paintable when fully dry. During curing product will show minimal shrinkage, which can cause cracking of the paint. Paintable with water based and synthetic paints. Painting with highly water based paints can create cracking. We recommend testing compatability with paint prior to application.

**Cleaning**

Tools to be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

**Additional Information**

Application temperature		+5°C to +30°C
Base		Acrylic dispersion
Density		0,57 g/ml
Flow	ISO 7390	<2mm
Frost resistance during transportation		Down to -15°C
Shrinkage		<5%
Skin formation	@ +23°C/50% RH	5 Minutes
Temperature resistance		-20°C to +75°C

These values are typical properties and may vary +/-3%

**Shelf Life**

In unopened original packaging between + 5°C and +25°C, shelf life till 12 months after production date, stored in a dry place.

**Certification**

	Emicode EC1 Plus M1 EN 13963: 1A
--	--

**Health & Safety**

Safety data sheet (MSDS) must be read and understood before use of product. These are available on request.