

# Technical Specification

**Product Code:** VPCH522WH

**Description:** 20A Ingot Double Pole Plate Switch With Optional Flex Outlet



Representative Image

## General Information

|                                   |   |
|-----------------------------------|---|
| <b>Dimensions</b>                 | 88mm (W) x 88mm (H) x 8mm (D)   |
| <b>Dimensions With Gasket</b>     | 91mm (W) x 91mm (H) x 9mm (D)   |
| <b>Plate Design &amp; Finish</b>  | Victorian Polished Chrome   |
| <b>Insert &amp; Gasket Colour</b> | White   |
| <b>Materials</b>                  | Front Plate: Stainless Steel<br>Insert & Housing: Urea<br>Switch Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass<br>Earth Strap: Mild Steel<br>Gasket: Nylon |
| <b>Maximum Voltage</b>            | 250V~ 50Hz  |
| <b>Load Rating</b>                | 20A   |
| <b>Plate Fixing Centres</b>       | 60.3mm  |
| <b>Terminal Size</b>              | 5mmø  |
| <b>Terminal Torque</b>            | 1.8Nm   |
| <b>Terminal Capacity</b>          | 4 x 2.5mm <sup>2</sup>  |
| <b>Double Pole</b>                | Yes   |
| <b>Twin Earth Terminals</b>       | Yes   |
| <b>Flex Outlet</b>                | Yes (10mmø Through Front of the Plate)  |
| <b>Ingress Protection</b>         | IP20  |
| <b>Back Box Depth</b>             | 25mm Minimum  |
| <b>Operational Temperature</b>    | -5°C to +40°C   |
| <b>Warranty</b>                   | 10 Years  |

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

## Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.