



Replaces a traditional 400W HID industrial fixture with just 150W of LED

Providing over 65% energy savings

Efficient aluminium heatsink, extending product life

Up to 30,000 lumen output

Market leading 150lm/W

IP65 rated

IK08 rated impact resistance

Optional reflectors available

Optional polycarbonate lens suitable for food production areas

Market leading efficiency







60° Aluminium





90° Aluminium Mounting Bracket

Cat. No.	Watts	Colour	Lumens	lm/W
1-10V Dimmable				
EN-HB100C*/40	100W	4000K	15000lm	150
EN-HB150C*/40	150W	4000K	22500lm	150
EN-HB200C*/40	200W	4000K	30000lm	150

Accessories

EN-HBACR2 70° Highbay Polycarbonate Reflector
EN-RF601 60° Highbay Aluminium Reflector
EN-RF901 90° Highbay Aluminium Reflector
EN-HBMB1 Highbay Mounting Bracket

*Add suffix **D** for **Diffuser** for use in food production areas For emergency option please contact sales.











5 Year Warranty

L70 50,000hrs

1-10V dimmable as standard

Emergency option

Black finish

make mart with

works with

.control




1-10V Inline Dimmer See pg.45



On/Off Relay See pg.47

EN-HB150C





EN-HB100C / EN-HB150C

(H) 193mm Height (OD) 252mm Overall (Ø)

EN-HB200C

(H) 208mm Height (OD) 295mm Overall (Ø) Eyelet internal diameter is 15mm



