



Technical Specification

Product Code: VPSB038BK

Description: 5A Round Pin Socket Outlet





General Information

Dimensions88mm (W) × 88mm (H) × 8mm (D)Dimensions With Gasket91mm (H) × 91mm (H) × 9mm (D)Plate Design & FinishVictorian Satin BrassInsert & Gasket ColurBlackMaterialFront Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminal: BrassMaterialGood Steel Casket: Nylon Terminal: Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: NylonMaximum Voltage250/~ 50HzLoad Rating5APlate Fixing Centres60.3mmOf Terminal Size5mmedSwitchedNoTerminal Size5mmedSwitchedNoIngress ProtectionIP20Back Box Depth25mm MinimumTermination TypeScrewOperational Temperatur Termination TypeScrewStandards85 546: 1950Additional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal Bare earth cables must always be covered with appropriate sleeving		
Plate Design & Finish Victorian Satin Brass Insert & Gasket Colour Black Materials Front Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminals: Brass Terminals: Brass Terminal: Brass Terminal: Steel Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon Terminal Steel Load Rating 5A Plate Fixing Centres 60.3mm Terminal Stee Smme Terminal Capacity 4 x 1.5mm² or 3 x 2.5mm² Switched No Ingress Protection IP20 Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950	Dimensions	88mm (W) x 88mm (H) x 8mm (D)
Insert & Gasket Colour Black Materials Front Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbara: Formed Pressed Brass Earth Strap: Mild Steel Gasket: Nylon Maximum Voltage 250V- 50Hz Load Rating 5A Plate Fixing Centres 60.3mm Terminal Size 5mme Terminal Capacity 4 x 1.5mm ² or 3 x 2.5mm ² Switched No Twin Earth Terminals No Ingress Protection IP20 Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Dimensions With Gasket	91mm (W) x 91mm (H) x 9mm (D)
MaterialsFront Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminal: Brass Terminal: Brass Terminal: Brass: Terminal: Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Gasket: NylonMaximum Voltage250V 50Hz Load RatingLoad Rating5APlate Fixing Centres60.3mmTerminal Size5mmedTerminal Torque1.2NmTerminal Torque1.2NmTerminal Capacity4 x 1.5mm² or 3 x 2.5mm² SwitchedSwitchedNoIngress ProtectionIP20Back Box Depth25mm Minimum ScrewOperational Temperature-5°C to +40°C VarrantyWarranty10 YearsAdditional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Plate Design & Finish	Victorian Satin Brass
Insert: Urea Rear Housing: Nylon Terminals: Brass Terminal: Strass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Stray: Mid Steel Gasket: Nylon Maximum Voltage 250V~ 50Hz Load Rating 5A Plate Fixing Centres 60.3mm Terminal Size 5mmø 1erminal Torque 1.2Nm Terminal Torque 1.2Nm Terminal Capacity 4 x 1.5mm² or 3 x 2.5mm² Switched No Twin Earth Terminals No Ingress Protection IP20 Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to + 40°C Warranty 10 Years Standards BS 546: 1950 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Insert & Gasket Colour	Black
Load Rating5APlate Fixing Centres60.3mmTerminal Size5mmøTerminal Torque1.2NmTerminal Capacity4 x 1.5mm² or 3 x 2.5mm²SwitchedNoTwin Earth TerminalsNoIngress ProtectionIP20Back Box Depth25mm MinimumTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS 546: 1950Additional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Materials	Insert: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Plate Fixing Centres60.3mmTerminal Size5mmøTerminal Torque1.2NmTerminal Capacity4 x 1.5mm² or 3 x 2.5mm²SwitchedNoTwin Earth TerminalsNoIngress ProtectionIP20Back Box Depth25mm MinimumTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS 546: 1950Additional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Maximum Voltage	250V~ 50Hz
Terminal Size5mmøTerminal Torque1.2NmTerminal Capacity4 x 1.5mm² or 3 x 2.5mm²SwitchedNoTwin Earth TerminalsNoIngress ProtectionIP20Back Box Depth25mm MinimumTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS 546: 1950Additional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Load Rating	5A
Terminal Torque1.2NmTerminal Capacity4 x 1.5mm² or 3 x 2.5mm²SwitchedNoTwin Earth TerminalsNoIngress ProtectionIP20Back Box Depth25mm MinimumTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS 546: 1950Additional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Plate Fixing Centres	60.3mm
Terminal Capacity4 x 1.5mm² or 3 x 2.5mm²SwitchedNoTwin Earth TerminalsNoIngress ProtectionIP20Back Box Depth25mm MinimumTermination TypeScrewOperational Temperature-5°C to +40°CWarranty10 YearsStandardsBS 546: 1950Additional InformationEnsure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		5mmø
Switched No Twin Earth Terminals No Ingress Protection IP20 Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Terminal Torque	1.2Nm
Twin Earth Terminals No Ingress Protection IP20 Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		4 x 1.5mm ² or 3 x 2.5mm ²
Ingress Protection IP20 Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	•••••••	No
Back Box Depth 25mm Minimum Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Twin Earth Terminals	No
Termination Type Screw Operational Temperature -5°C to +40°C Warranty 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Ingress Protection	IP20
Operational Temperature Warranty -5°C to +40°C 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		25mm Minimum
Warranty 10 Years Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		
Standards BS 546: 1950 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.		
Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	Warranty	10 Years
diagram with the relevant product.	Standards	BS 546: 1950
	Additional Information	diagram with the relevant product.

UK Design Registration: 3015621