

Blade™

Linear Interconnectable Undercabinet LED Striplight

make smart with



See pg.256-258 for compatibility table

- Slim profile
- Plug in power lead
- Supplied with mounting clips
- Multiple lengths can be connected using link leads or the connectors
- On/off touch switch allows independent control of interconnected fittings
- PIR detection distance up to 1 metre, detection range 60° (sold separately)
- Time adjustable to 1 minute or 5 minutes

- 3 Year Warranty
- L70 30,000hrs
- PIR sensing option
- Silver finish



works with


.control



On/Off Relay
see pg.47



EN-CLA1
Connector Bar




EN-CLA2
Corner Connector Bar



EN-CLA3
Interconnection Lead



EN-CLPIR
PIR Sensor



EN-CL55T
(L) 500mm Length
(W) 25mm Width
(H) 9mm Height

EN-CL85T (L) 800mm Length
(W) 25mm Width
(H) 9mm Height

EN-CL105T (L) 1000mm Length
(W) 25mm Width
(H) 9mm Height

Cat. No.	Watts	Colour	Lumens	lm/W
EN-CL55T/30	5.5W	3000K	310lm	56
EN-CL55T/40	5.5W	4000K	330lm	60
EN-CL85T/30	8.5W	3000K	480lm	56
EN-CL85T/40	8.5W	4000K	520lm	61
EN-CL105T/30	10.5W	3000K	590lm	56
EN-CL105T/40	10.5W	4000K	640lm	61

Cat. No. Description

Accessories

- [EN-CLA1](#) Blade™ Connector Bar
- [EN-CLA2](#) Blade™ Corner Connector Bar
- [EN-CLA3](#) Blade™ 155mm Interconnection lead
- [EN-CLA4](#) Blade™ 500mm Interconnection lead
- [EN-CLP1](#) Blade™ 2m Mains Lead Without Plug
- [EN-CLPIR](#) Blade™ PIR Sensor

Cat. No.	AU-LED1012CV	AU-LED16T	AU-LED2512CV	EN-LED7512
----------	--------------	-----------	--------------	------------

LED Drivers

EN-CL55T	1	2	3	10
EN-CL85T	1	1	2	6
EN-CL105T	-	1	2	5



Undercabinet