

make smart with See pg.256-258 for compatibility table

1 Year Warranty

L70 10,000hrs

316 Stainless Steel finish

316 stainless steel

IP68 rated

Pre-wired with 1 metre of rubber cable

Submersible to a depth of 1 metre

For installation, wire in series only



works with

.control



EN-WU682R (OD) 31mm Overall Ø (H) 40mm Height EN-WU682S (LxW) 30 x 30mm (H) 40mm Height EN-WU673R (OD) 31mm Overall Ø (H) 60mm Height

On/Off Relay See pg.47











1W Round

1W Square

3W Round

350mA OR 700mA see pg.246

Watts No. of Colour Lumens No. of Fittings per driver Cutout Input Type Cat. No. LEDs $[\emptyset]$

AU-LED09IP AU-LED709IP

| EN-WU682R/3 | 1W | 1 | 3000K | 80lm | 1-5 | - | 26mm | 350mA | Round |
|--------------|------|---|-------|-------|-----|-----|------|-------|--------|
| EN-WU682R/5 | 7 1W | 1 | 5700K | 80lm | 1-5 | - | 26mm | 350mA | Round |
| EN-WU682R/BL | U 1W | 1 | Blue | - | 1-5 | - | 26mm | 350mA | Round |
| EN-WU682S/4 | 1W | 1 | 4000K | 80lm | 1-5 | - | 26mm | 350mA | Square |
| EN-WU673R/3 | 3W | 1 | 3000K | 130lm | - | 1-3 | 26mm | 700mA | Round |
| EN-WU673R/5 | 3W | 1 | 5500K | 130lm | - | 1-3 | 26mm | 700mA | Round |













