



See pg.256-258 for compatibility table

High density single colour flexible LED strip with 3M™ self adhesive backing

Cut points every 50mm for maximum flexibility

Beam angle of 120° and 9mm between LEDs, 120 LEDs per metre

Voltage drop of 4.5V per 10m and maximum run of 10m

For runs over 10m individual lengths should be connected in parallel

Reel length of 30m





Cat. No.	Watts/m	No. of LEDs/m	Colour	lm/m
EN-ST224/27	9.6W	120	2700K	960lm
EN-ST224/30	9.6W	120	3000K	960lm
EN-ST224/40	9.6W	120	4000K	1027lm
EN-ST224/60	9.6W	120	6300K	1084lm
FN-ST224/BLU	9.6W	120	Blue	_

Accessories

LEDLine™ PRO Single Colour Strip Connector EN-ST224A LEDLine™ PRO Single Colour Wired Strip Connector EN-ST224B

EN-ST224C LEDLine™ PRO Single Colour Inter-Connection Strip Connector 3 Year Warranty

L70 35,000hrs

2700K, 3000K, 4000K, 6300K & Blue colour options





.control



12/24V Inline Controller see pg.43



On/Off Relay see pg.47









Cat. No.	Description	Metres per driver
LED Drivers		

AU-LED1624CV 16W Non-Dimmable 24V Constant Voltage Driver 1m EN-LED7524 75W Non-Dimmable 24V Constant Voltage Driver 5m EN-LEDD7524 75W Triac Dimmable 24V Constant Voltage Driver 5m 100W IP67 Non-Dimmable 24V Constant Voltage Driver 10m AU-ELG-100-24

For alternative lengths see pg.245







