


Product Code: QCT06-6

Description: 6mm² Copper Tube Lug With 6mm Stud



Dimensions (mm)

| ØA | B | D | ØE | F | G | J | K |
|-----|---|----|-----|---|---|----|---|
| 3.8 | 9 | 12 | 6.5 | 1 | 6 | 27 | 3 |

Materials

Tin Plated Copper Tube

General Information

| | |
|----------------------|------------------------------|
| Conductor Cable Size | 6mm ² |
| Fixing Type | Suitable for crimp or solder |
| Inspection Window | Yes |
| Contact Plating | 5 to 8 Microns |
| Flared Entry | Yes |
| Conductivity | 97% to IACS |
| Working Temperature | Up to 180°C |

Additional Information

When using flexible fine strand or welding cable it may be necessary to select the next larger terminal size, i.e 70mm² fine strand, select 95mm² terminal.

Packaging Overview

Polybag Of 25 Lugs

Standards

ANSI/UL 486A-486B, CAN/CSA-C22.2 No. 65
ANSI/UL 486C, CSA-C22.2 No. 188
Tensile performance requirements to IEC 61238-1-1: 2018

Directives

Low Voltage Directive: 2014/35/EU
RoHS 2: 2011/65/EU & RoHS 3: 2015/863/EU
REACH: 1907/2006/EU

