

# PVC Corrugated Conduit & Fittings – 15D

Pliable conduit light gauge non flame propagating in accordance with EN50086-2-2 IEC61386-22.

Temperature -5°C to +60°C.

Colours available in conduit: Black, White, Grey, Orange.

### Fittings:

IP40 Flexible conduit gland manufactured from nylon 6/6.

IP68 Flexible conduit gland two piece design ensures good mechanical strength.

CL CLIP Halogen free interlinkable clip, simply push conduit to fit.



Part No.	Description
M20CONN	100m Coil M20
M25CONN-50M	50m Coil M25
M20SPLIT-UNI	M20 Universal gland
M25SPLIT-UNI	M25 Universal gland
M20CONNGLAND	M20 IP68 Conduit gland
M25CONNGLAND	M25 IP68 Conduit gland
CL20SW	Conduit clip
CL25SW	Conduit clip

Sizes to M50 available.

# Liquid Tight Conduit & Fittings – 15E

Galvanised steel flexible conduit with smooth oil resistant high temperature PVC coating.

Temperature rating: -20°C to 105°C

IP Rating: IP68

\*Nickel plated brass or stainless steel fittings available.



Part No.	Description
LT20	20mm Liquid tight conduit
LT25	25mm Liquid tight conduit
LT32	32mm Liquid tight conduit
LT20NPG	20mm Nickel plated brass gland IP68
LT25NPG	25mm Nickel plated brass gland IP68
LT32NPG	32mm Nickel plated brass gland IP68

Sizes to M50 available.

# Split Conduit – 15F

PVC Split conduit.

Ideal for repair or containment of existing cabling without disconnecting cables.

Part No.	Internal Ø mm	Coil size m
RS07B	6.9	50
RS12B	10.1	50
RS16B	12.9	50
RS20B	17.0	50
RS25B	20.0	50

