

Resin Cable Joint Kits – 7A

Click seal resin filled joints for voltages up to 3.6kV.

Easy to install, click together moulds.

Mechanical connectors up to 400mm².

Complete range of joints from 0.75mm - 400mm².

Available in both straight and branch formats.

Suitable for single and multiple polymeric and paper cables

both stranded and solid copper/aluminium connectors.

Performance tested to BS6910/HD623 / VDE0278.



Kit selection for LV straight joints 2/3/4 core cables to BS5467 (SWA)

Kit No.	Cable Size mm ²	Cable Diameter mm
JK075-4	1.5, 2.5 Suitable for unarmoured cable only	6-15
JK1.5-10	1.5, 2.5, 4, 6, 10	8-20
JK10-25	10, 16, 25	13-25
JK25-50	25, 35, 50	18-30
JK70-120	70, 95, 120	25-45
JK150-240	150, 185, 240	45-60
JK300-400	300, 400	50-100

Kit selection for LV multipair telephone cables

Kit No.	Cable Size mm	Pair No.	Cable Diameter mm
JK075-4	0.9	2pair Suitable for unarmoured cable only	6-15
JK1.5-10	0.9	2pair, 5pair, 10pair	8-20
JK10-25	0.9	15pair, 25pair	13-25
JK70-120	0.9	25pair, 40pair	25-45
JK150-240	0.9	50pair, 100pair	45-60

Kit selection for LV branch joints 2/3/4 core cables

Kit No.		Cable Size mm ²	Cable Diameter mm
JKB4	Main cable	1.5, 2.5, 4 Suitable for unarmoured cable only	6-15
	Branch cable	1.5, 2.5	6-15
JKB10	Main cable	4, 6, 10	8-20
	Branch cable	1.5, 2.5, 4, 6, 10	8-20
JKB25	Main Cable	10, 16, 25	13-30
	Branch cable	1.5, 2.5, 4, 6, 10, 16, 25	8-25
JKB50	Main cable	25, 35, 50	18-30
	Branch cable	1.5, 2.5, 4, 6, 10, 16, 25, 35	8-35
JKB120	Main cable	50, 70, 95, 120	25-45
	Branch cable	1.5, 2.5, 4, 6, 10, 16, 25, 35	8-35
JKB240	Main cable	120, 150, 185, 240	45-60
	Branch cable	1.5, 2.5, 4, 6, 10, 16, 25, 35	8-35
JKB400	Main cable	240, 300, 400	50-100
	Branch cable	1.5, 2.5, 4, 6, 10, 16, 25, 35	8-35