

Adhesive Lined Heatshrink 3/1 Ratio – 3B

Flexible flame retardent polyolefin with an inner liner of hot melt adhesive.
 This 3/1 ratio tubing is ideal for waterproofing and encapsulation of harnesses.
 Continuous operating temperature -55°C to 135°C.
 MIL-DTL-23053/5.



Part No.	Recovered mm
ADL3.2	1.1
ADL4.8	1.6
ADL6.4	2.2

Part No.	Recovered mm
ADL9.5	3.2
ADL12.7	4.2
ADL19.1	6.4

Part No.	Recovered mm
ADL25.4	8.4
ADL38	12.7
ADL50	16.5

Medium Wall Adhesive Lined Heatshrink 3/1 Ratio – 3B

High resistance to abrasion, corrosion & chemicals.
 Continuous operating temperature -55°C to +110°C.
 Shrink temperature 120°C.
 Performance tested UL224.



Part No.				
MWTM12/4	MWTM16/5	MWTM22/6	MWTM28/6	MWTM33/8
MWTM45/12	MWTM56/18	MWTM65/19	MWTM75/22	MWTM90/30

Heatshrink Endcaps – 3C

Heatshrink endcaps are manufactured from polyolefin material coated with a hot melt adhesive to provide a watertight seal. Also offering excellent resistance against abrasion.



Part No.	Internal diameter mm
EC14/4	14
EC25/8	25
EC40/14	40

Part No.	Internal diameter mm
EC55/25	55
EC80/25	80
EC100/57	100