

# JC71745 Skypack QR LED batten 6ft single IP20 54W 4000K 6480lm



#### **Features & Benefits**

Intelligent press release buttons for simple installation

Ultra efficient, up to 120 lumens per circuit Watt

Suitable for temperatures -10°C to 50°C

Press fit terminals, loop in loop out

Rear and end conduit entry points

Suspended LED tray for easy installation

#### **General Information**

Product Group	LED - Surface
Product Range	Skypack
Trade Name	Skypack
Light Source	LED

#### **JCC Lighting**

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Light Source Features	Neutral White
Lighting Product Type	Linear Lighting
Product Shape	Rectangular
Mounting	Surface Mounted
Product Weight	2.63kg
Color Finish	White
Overall Dimensions	1828 x 70 x 76.5
Recommended Product Location	Domestic, Commercial and Industrial Applications
Method Of Fix	Surface with Conduit Entry
IP Rating	IP20
Environment	Indoor
Origin Of Manufacture	Made In China
Guarantee	3 years
Driver Manufacturer	Ledtu
LED Manufacturer/Type	Runlite

## **Electrical**

Voltage Rating	220-240
Secondary Running Current	1050mA
Primary Running Current	350mA
Operating Frequency (Hz)	50/60Hz
CC or CV	Constant Current
Luminaire Circuit Wattage	54
Sec - Voltage (V)	27-40VDC
Class	Class I: requires an Earth connection
EMC Compliant (EN55015)	Yes

#### **JCC Lighting**

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Power Factor Correction	0.9
Input Electrical Connections	Live, Earth & Neutral
Dimmable	No

## Thermals

Room Ambient Temperature Not To Exceed

30°C

#### Performance Data

Energy Rating	A+
Actual Lumen Output	6480
Lumen Output	5001-8000
Lumens Per Circuit Watt	120
LED Life (Hours)	36000
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	4000K
Light Distribution Detail	120-degree
LOR (Light Output Ratio) %	100
Photometry Available	Yes

## Construction

Primary Material	Steel
Diffuser	Polycarbonate

## **Packaging**

Quantity Per Outer Carton	8
Bar Code EAN Number	5052544080487

#### **JCC Lighting**

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Packaged Weight 3.1	.7kg
---------------------	------

## Standards & Approvals

Listings	CE
Manufactured In Accordance To	BS EN 60598:2015, 2-1
CE Marked	Yes
Batch Coded	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Yes: available on request.
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

Datasheet generated from https://www.electrika.cloud on 10 September 2018 14:33:00