

# Spring Steel Fasteners – 24A

New expanded 'M' range of spring steel fasteners.

Part No.	Walraven	Description	Flange mm	Qty
M-BE24	BC250	Flange beam fastener	3-8	25
M-BE58	BC500	Flange beam fastener	8-14	25
M-BE912	BC750	Flange beam fastener	14-20	25
M-BU24	H24	Universal beam clamp	3-8	25
M-BU58	H58	Universal beam clamp	8-14	25
M-BMU24S	H24S	Universal beam fastener	3-8	25
M-BMU58S	H58S	Universal beam fastener	8-14	25
M-BF1	VF1	Vertical flange hanger	14-20	25

Part No.	Walraven	Description	Flange mm	Qty
M-BE24CT	BCCT25R	Rod to beam hanger	3-8	25
M-BE58CT	BCCT50R	Rod to beam hanger	8-14	25
M-BMA416	AC25	T bar clip	25	25
M-BC1	MC10	Beam clamp	18	25

Part No.	Walraven	Description	Flange mm	Cable mm	Qty
M-BXS89	CR47	Cable fastener	2-4	8-9	25
M-BXS1011	CR210	Cable fastener	2-4	10-11	25
M-BXS1214	CR212	Cable fastener	2-4	12-14	25
M-BXS1519	CR215	Cable fastener	2-4	15-19	25
M-BXS2024	CR219	Cable fastener	2-4	20-24	25
M-BXS2530	CR225	Cable fastener	2-4	25-30	25
M-BXM67	CR86	Cable fastener	4-7	6-7	25
M-BXM89	CR47	Cable fastener	4-7	8-9	25
M-BXM1011	CR410	Cable fastener	4-7	10-11	25
M-BXM1214	CR412	Cable fastener	4-7	12-14	25
M-BXM1519	CR415	Cable fastener	4-7	15-19	25
M-BXM2024	CR419	Cable fastener	4-7	20-24	25
M-BXM2530	CR425	Cable fastener	4-7	25-30	25
M-BXL67	CR46	Cable fastener	8-12	6-7	25
M-BXL89	CR87	Cable fastener	8-12	8-9	25
M-BXL1011	CR810	Cable fastener	8-12	10-11	25
M-BXL1214	CR812	Cable fastener	8-12	12-14	25
M-BXL1519	CR815	Cable fastener	8-12	15-19	25
M-BXL2024	CR819	Cable fastener	8-12	20-24	25
M-BXL2530	CR825	Cable fastener	8-12	25-30	25



BE



BU



BF1



BECT



BMAX



BC1



BXS



BXM



BXL

## Kwik Wire™ Pak – 24B

The new KwikWire™ Hanging system, now available in handy sized packs.

- Installs up to 50% faster – can wrap around beam with no drilling required.
- Simple height adjustments are made by releasing the clamps adjustment pin – no tools required.
- Aesthetic appeal – blends in with upper structural supports.
- Compatibility with many B-Line fastener, anchor and hanger products.
- Ideal for sloped ceiling applications – will support loads at up to a 60° angle from vertical.

