

Copper Tube Lugs (T Range) - Termination Technology Limited

Part No.	Conductor Size mm ²	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d _ø
T1.5-3	1.5	3	17	5.5	1.8	3.2
T1.5-4	1.5	4	19.5	6.7	1.9	4.3
T1.5-5	1.5	5	20.4	7.7	1.8	5.3
T2.5-3	2.5	3	18	5.5	2.4	3.2
T2.5-4	2.5	4	19	8	2.4	4.3
T2.5-5	2.5	5	21.2	10	2.4	5.3
T2.5-6	2.5	6	21	10	2.4	6.5
T4-4	4	4	21	10	3	4.3
T4-5	4	5	22	10	3	5.3
T4-6	4	6	23.5	10	3	6.5
T6-4	6	4	21.5	9.5	4.1	4.3
T6-5	6	5	24.5	10	4.1	5.3
T6-6	6	6	24.5	11	4.1	6.3
T6-8	6	8	27	12.5	4.1	8.3
T6-10	6	10	29	12.5	4.1	10.3
T6-BL	6	-	29	12.5	4.1	-
T10-5	10	5	26	10.8	4.4	5.1
T10-6	10	6	26	10.8	4.4	6.3
T10-8	10	8	29.5	13.5	4.4	8.2

Part No.	Conductor Size mm²	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d_ø
T10-10	10	10	39	15	4.4	10.4
T10-12	10	12	39	18	4.4	12.7
T10-BL	10	-	39	18	4.4	-
T16-5	16	5	30	10.8	5.6	5.2
T16-6	16	6	30	10.8	5.6	6.3
T16-8	16	8	30	13.5	5.6	8.3
T16-10	16	10	35.5	15	5.6	10.3
T16-12	16	-	42	18	5.6	-
T25-5	25	5	32.5	13.8	7	5.2
T25-6	25	6	32.5	13.8	7	6.3
T25-8	25	8	32.5	13.8	7	8.2
T25-10	25	10	38	16	7	10.2
T25-12	25	12	38	18	7	12.8
T25-BL	25	-	38	16	7	-
T35-5	35	5	35	15.3	8.2	5.2
T35-6	35	6	35	15.3	8.2	6.3
T35-8	35	8	35	15.3	8.2	8.3
T35-10	35	10	40.5	15.3	8.2	10.3
T35-12	35	12	40.5	18	8.2	12.9
T35-14	35	14	40.5	19.6	8.2	14.8
T35-BL	35	-	40.5	18	8.2	-
T50-6	50	6	37	17.4	9.5	6.3
T50-8	50	8	37	17.4	9.5	8.3

Part No.	Conductor Size mm²	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d_ø
T50-10	50	10	42.5	17.4	9.5	10.3
T50-12	50	12	42.5	17.4	9.5	12.8
T50-14	50	14	42.5	20.3	9.5	14.8
T50-16	50	16	52.8	23.2	9.5	16.5
T50-BL	50	-	42.5	17.4	9.5	-
T70-6	70	6	40.5	20.9	11.5	6.3
T70-8	70	8	40.5	20.9	11.5	8.2
T70-10	70	10	46	20.9	11.5	10.2
T70-12	70	12	46	20.9	11.5	12.7
T70-14	70	14	50	20.9	11.5	14.8
T70-16	70	16	50	20.9	11.5	16.3
T70-20	70	20	71.9	30	11.5	20.9
T70-BL	70	-	50	20.9	11.5	-
T95-6	95	6	49.5	24.3	13.5	6.3
T95-8	95	8	49.5	24.3	13.5	8.3
T95-10	95	10	49.5	24.3	13.5	10.3
T95-12	95	12	49.5	24.3	13.5	12.7
T95-14	95	14	56	24.3	13.5	14.8
T95-16	95	16	56	24.3	13.5	16.3
T95-20	95	20	73.6	30	13.5	20.9
T95-BL	95	-	56	24.3	13.5	-
T120-8	120	8	55.5	27.3	15	8.3
T120-10	120	10	55.5	27.3	15	10.3

Part No.	Conductor Size mm²	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d_ø
T120-12	120	12	55.5	27.3	15	12.7
T120-14	120	14	55.5	27.3	15	14.8
T120-16	120	16	60	27.3	15	16.3
T120-20	120	20	76.6	30	15	20.9
T120-BL	120	-	55.5	27.3	15	-
T150-8	150	8	61	30.2	16.5	8.3
T150-10	150	10	61	30.2	16.5	10.2
T150-12	150	12	61	30.2	16.5	12.7
T150-14	150	14	61	30.2	16.5	14.7
T150-16	150	16	65	30.2	16.5	16.2
T150-20	150	20	65	30.2	16.5	20.8
T150-BL	150	-	65	30.2	16.5	-
T185-10	185	10	66.5	33.3	18.5	10.3
T185-12	185	12	68	33.3	18.5	12.9
T185-14	185	14	68	33.3	18.5	14.7
T185-16	185	16	70	33.3	18.5	16.5
T185-20	185	20	70	33.3	18.5	20.9
T185-BL	185	-	70	33.3	18.5	-
T240-10	240	10	88	37.7	21	10.3
T240-12	240	12	88	37.7	21	12.7
T240-14	240	14	88	37.7	21	14.7
T240-16	240	16	88	37.7	21	16.4
T240-20	240	20	88	37.7	21	20.9

Part No.	Conductor Size mm²	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d_ø
T240-BL	240	-	88	37.7	21	-
T300-10	300	10	97	41	23	10.3
T300-12	300	12	97	41	23	12.7
T300-14	300	14	97	41	23	14.7
T300-16	300	16	97	41	23	16.4
T300-20	300	20	97	41	23	20.9
T300-BL	300	-	97	41	23	-
T400-12	400	12	108	47.3	27	12.7
T400-14	400	14	108	47.3	27	14.7
T400-16	400	16	108	47.3	27	16.4
T400-20	400	20	108	47.3	27	20.9
T400-BL	400	-	108	47.3	27	-
T500-14	500	14	117	53	30	14.7
T500-16	500	16	117	53	30	16.4
T500-20	500	20	117	53	30	20.9
T500-BL	500	-	117	53	30	-
T630-16	630	16	127	63	33.8	16.4
T630-20	630	20	127	63	33.8	20.9
T630-BL	630	-	127	63	33.8	-
T800-20	800	20	164	70	38	20.9
T800-BL	800	-	164	70	38	-
T1000-20	1000	20	169	77	42.5	20.9

Part No.	Conductor Size mm²	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d_ø
T1000-BL	1000	-	169	77	42.5	-