

## Stainless Steel Skintop Glands – 4L

316 Grade dome top gland.  
Offering an IP68 rating.

| Part No.      | Min / Max cable range mm |
|---------------|--------------------------|
| <b>M16-SS</b> | 4 - 8                    |
| <b>M20-SS</b> | 6 - 12                   |
| <b>M25-SS</b> | 10 - 14                  |
| <b>M32-SS</b> | 13 - 18                  |
| <b>M40-SS</b> | 18 - 25                  |
| <b>M50-SS</b> | 22 - 32                  |



## Nickel Plated EMC Glands – 4L

Brass dome top nickel plated EMC gland.  
Ideal for watertight applications.  
High quality finish suitable for plant machinery and control equipment.  
Offering an IP68 rating.

| Part No.             | Min / Max cable range mm |
|----------------------|--------------------------|
| <b>M20 EMC GLAND</b> | 6 - 12                   |
| <b>M25 EMC GLAND</b> | 10 - 14                  |
| <b>M32 EMC GLAND</b> | 13 - 18                  |
| <b>M40 EMC GLAND</b> | 18 - 32                  |



## Nylon IP68 Skintop Glands Metric – 4M

Nylon IP68 skintop cable glands.  
Available in a selection of colours.  
Sizes range from M12 to M63.  
Operation temperature -40°C to +100°C.  
Thermoplastic rubber seal.  
Conforms to EN50262.

| Part No.      | Min / Max cable range mm |
|---------------|--------------------------|
| <b>NGM12</b>  | 2 - 7                    |
| <b>NGM16</b>  | 4 - 8                    |
| <b>NGM20S</b> | 4 - 10                   |
| <b>NGM20</b>  | 6 - 12                   |
| <b>NGM20L</b> | 10 - 14                  |
| <b>NGM25</b>  | 13 - 18                  |
| <b>NGM32</b>  | 18 - 25                  |
| <b>NGM40</b>  | 22 - 32                  |
| <b>NGM50</b>  | 30 - 38                  |
| <b>NGM63</b>  | 34 - 44                  |



## Nylon IP68 Skintop Glands PG – 4M

Nylon IP68 skintop cable glands.  
Available in a selection of colours.  
Sizes range from PG7 to PG48.  
Operation temperature -40°C to +100°C  
Thermoplastic rubber seal.  
Manufactured to EN50262.  
Conforms to EN50262.

| Part No.        | Min / Max cable range mm |
|-----------------|--------------------------|
| <b>NGPG7</b>    | 3 - 6.5                  |
| <b>NGPG9</b>    | 4 - 8                    |
| <b>NGPG11</b>   | 5 - 10                   |
| <b>NGPG13.5</b> | 6 - 12                   |
| <b>NGPG16</b>   | 10 - 14                  |
| <b>NGPG21</b>   | 13 - 18                  |
| <b>NGPG29</b>   | 18 - 25                  |
| <b>NGPG36</b>   | 22 - 32                  |
| <b>NGPG42</b>   | 30 - 38                  |
| <b>NGPG48</b>   | 34 - 44                  |

