

PVC Sleeving – 3J

PVC Sleeving to BS2848 type 3 class 85T supplied in 100m coils.
 0.5mm wall thickness.
 Self extinguishing -20°C to +85°C.
 Colours available: Black, grey, blue, red, brown, white, green/yellow.
 Size range ID: 2mm, 3mm, 4mm, 6mm, 10mm, 15mm.



PVC Sleeve Packs – 3J

PVC Sleeving to BS2848 type 3 class 85T supplied in 5m packs.
 0.5mm wall thickness.
 Self extinguishing -20°C to +85°C.
 Colours available: Black, grey, blue, red, brown, green/yellow.



PVC Size	Example	Part No.
4mm	Colour P5	PVC4G/YP5

PVC Sleeving Drums – 3J

PVC Sleeving to BS2848 type 3 class 85T supplied on 100m drums.
 0.5mm wall thickness.
 Self extinguishing -20°C to +85°C.
 Colours available: Black, grey, blue, brown, green/yellow.
 Size range ID: 2mm (green/yellow only), 3mm, 4mm.



Grommet Strip – 3K


Smooth edged LDPE Grommet strip.
 Suitable for a range of panel thickness 0.4mm to 3mm.

Part No.	Panel thickness	Length
GS1	0.4 - 1.0mm	35m
GS2	1.1 - 1.5mm	30m
GS3	1.6 - 2mm	25m
GS4	2.1 - 3mm	20m



Quick Fit Grommets – 3L

Push fit grommet seals are quick and easy to install, designed with a unique tapered flange to cut installation time by 50%.



Part No.		A - Panel Hole	B - Panel Thickness	C - Cable Hole
GROMMET20	20mm Open fast fit	19.6mm	1.9mm	15.9mm
GROMMET20CLOSED	20mm Closed fast fit	19.6mm	1.9mm	15.9mm
GROMMET25	25mm Open fast fit	24.8mm	2.1mm	19.6mm
GROMMET25CLOSED	25mm Closed fast fit	24.8mm	2.1mm	19.6mm
GROMMET32	32mm Open fast fit	32mm	1.6mm	23.8mm
GROMMET32CLOSED	32mm Closed fast fit	32mm	1.6mm	23.8mm
GROMMET38	38mm Open	38mm	1.6mm	31.8mm
GROMMET38CLOSED	38mm Closed	38mm	1.6mm	31.8mm
GROMMET50	50mm Open	50mm	1.6mm	44.4mm
GROMMET50CLOSED	50mm Closed	50mm	1.6mm	44.4mm