

Heatshrink 2/1 Ratio – 3A

Flexible polyolefin tubing designed for commercial use.

Common uses include, insulation, wire bundling, colour coding and mechanical protection.

Shrink ratio 2/1 in a range of sizes 1.2mm to 101mm.

Colours available Black, Blue, Brown, Clear, Green, Green/Yellow, Red, Violet, White, Yellow

Continuous operating temperature -55°C to 135°C

Flame retardant ULW-1 UL224/MIL-I-23053/5



Part No.	Recovered mm
HS1.2	0.6
HS1.6	0.8
HS2.4	1.2
HS3.2	1.6
HS4.8	2.4

Part No.	Recovered mm
HS6.4	3.2
HS9.5	4.8
HS12.7	6.4
HS19	9.5
HS25	12.7

Part No.	Recovered mm
HS38	19.0
HS50	25.4
HS75	38.0
HS101	50.0

Heatshrink Packs 2/1 Ratio – 3A

Flexible polyolefin tubing designed for commercial use.

Common uses include, insulation, wire bundling, colour coding and mechanical protection.

Shrink ratio 2/1 in a range of sizes 4.8mm to 50mm.

Colours in Pack - Black, Blue, Grey, Brown, Green/Yellow.



Part No.	Length Per Colour
HSP4NC	675mm
HSP6NC	675mm
HSP9NC	675mm
HSP12NC	675mm

Part No.	Length Per Colour
HSP19NC	675mm
HSP25NC	450mm
HSP38NC	450mm
HSP50NC	450mm

Heatshrink Boxes 2/1 Ratio – 3A

Flexible polyolefin tubing designed for commercial use.

Common uses include, insulation, wire bundling, colour coding and mechanical protection.

Shrink ratio 2/1 in a range of sizes 1.6mm to 25.4mm.

Colours available Black, Blue, Brown, Clear, Green, Green/Yellow, Red, Violet, White, Yellow.



Part No.	Size Internal mm	Box Size mtrs
HSB1.6	1.6	15m
HSB2.4	2.4	15m
HSB3.2	3.2	15m
HSB4.8	4.8	10m
HSB6.4	6.4	10m

Part No.	Size Internal mm	Box Size mtrs
HSB9.5	9.5	10m
HSB12.7	12.7	8m
HSB19	19.1	5m
HSB25	25.4	3m