

DELTA RANGE - IP20 LED Battens

- + IP20
- + Steel body construction, Opal polycarbonate diffusers
- + Integrated driver
- + High output options in the same footprint
- + Emergency options now available in 5ft & 6ft fittings
- + High LED chip efficiency
- + Compact design

**Now available in
Emergency Fittings**
- please see overleaf

TECHNICAL DATA SHEET



| | LEDBAT4 | LEDBAT5 | LEDBAT6 | LEDBAT4H | LEDBAT5H | LEDBAT6H |
|---------------------------|---|---------------------|---------------------|--------------------------|--------------------------|--------------------------|
| Description | 4ft Batten | 5ft Batten | 6ft Batten | 4ft Batten (High Output) | 5ft Batten (High Output) | 6ft Batten (High Output) |
| Barcode | 5012739645839 | 5012739645853 | 5012739645877 | 5012739645846 | 5012739645860 | 5012739645884 |
| Wattage | 18W | 24W | 32W | 36W | 48W | 64W |
| Power Rating | 220V/240V AC ~50Hz | | | | | |
| Colour Temperature | 4,000K | | | | | |
| Class | 1 | | | | | |
| IP Rating | IP20 | | | | | |
| Lamp Type | LED Non-replaceable | | | | | |
| Lumens | 1800 | 2400 | 3400 | 2900 | 4000 | 5200 |
| Beam Angle | 120° | | | | | |
| Main Housing | Steel Body with Polycarbonate Diffuser | | | | | |
| Dimensions | L1190 x W53 x H64mm | L1485 x W53 x H64mm | L1758 x W53 x H64mm | L1190 x W53 x H64mm | L1485 x W53 x H64mm | L1758 x W53 x H64mm |
| Mounting Options | BESA mount or Screw fixings | | | | | |
| Knockouts | 2 x 20mm at ends of fitting and 1 x 20mm at the back of fitting | | | | | |
| Weight (g) | 1030g | 1106g | 1278.5g | 1353g | 1529g | 1697.5g |
| Guarantee | 3 Years | | | | | |
| Conforms To | BS EN60598 | | | | | |

DELTA RANGE - IP20 LED Battens

Emergency Fittings

- + IP20
- + Steel body construction, Opal polycarbonate diffusers
- + Integrated driver
- + High output options in the same footprint
- + High LED chip efficiency
- + Compact design

Emergency Fittings
Greater than 3 hours emergency operation

TECHNICAL DATA SHEET



| | LEDBAT5EM | LEDBAT6EM | LEDBAT5HEM | LEDBAT6HEM |
|---------------------------|---|----------------------|------------------------------------|------------------------------------|
| Description | 5ft Emergency Batten | 6ft Emergency Batten | 5ft Emergency Batten (High Output) | 6ft Emergency Batten (High Output) |
| Barcode | 5012739647741 | 5012739647758 | 5012739647840 | 5012739647857 |
| Wattage | 24W | 32W | 48W | 64W |
| Power Rating | 220V/240V AC ~50Hz | | | |
| Colour Temperature | 4,000K | | | |
| Class | 1 | | | |
| IP Rating | IP20 | | | |
| Lamp Type | LED Non-replaceable | | | |
| Lumens | 2400 | 4000 | 3400 | 5200 |
| Beam Angle | 120° | | | |
| Ballast Type | LED Driver | | | |
| Battery Type | Ni-Cd, 6V, 3,000mAh | | | |
| Emergency Duration | More than 3 hours | | | |
| Main Housing | Steel Body with Polycarbonate Diffuser | | | |
| Dimensions | L1485 x W53 x H64mm | L1758 x W53 x H64mm | L1485 x W53 x H64mm | L1758 x W53 x H64mm |
| Mounting Options | BESA mount or Screw fixings | | | |
| Knockouts | 2 x 20mm at ends of fitting and 1 x 20mm at the back of fitting | | | |
| Weight (g) | 1811g | 2041g | 1857.5g | 2053g |
| Guarantee | 3 Years | | | |
| Conforms To | BS EN60598 | | | |