

Shower Fan Kits



Description

Shower fan kits include all parts necessary to complete the installation. The light version includes an option of either white or chrome bezels.

Features

- Low energy fans – meet Building Regulation L1A specific fan power of less than 0.5W/l/s
- Low noise fans – meet Building Regulation F1 by being under 35dB for less noise sensitive rooms
- Overrun timers factory set at 15 minutes
- Includes 3 metres of flexible ducting
- Round grille for fitting above shower, square grille for use outside
- Fans have a one shot thermal fuse
- 3 year guarantee

Range

- | | |
|---|------|
| 4" (100mm) Shower Fan Kit – timer | 4640 |
| 4" (100mm) Shower Fan Kit – light and timer | 4641 |

Standards

- BS EN 60335-2-80

Technical Specification

	Light Shower Fan	Shower Fan
Extraction Rate	30 l/s (107m ³ /hr)	30 l/s (107m ³ /hr)
Specific Fan Power	0.47W (l/s)	0.47W (l/s)
Noise Level	33dB @ 3m	33dB @ 3m
Voltage	240Vac	240Vac
Motor Rating	14W	14W
IP Rating	IP X4	IP X4
Ambient Temp	40°C max.	40°C max.
Insulation Class	Double Insulated	Double Insulated
Over Run Timer	2-30 mins.	2-30 mins.
Lamp	20W 12V	

No user serviceable parts

Deta Electrical Company Ltd.

Kingsway House Laporte Way
Luton Bedfordshires LU4 8RJ UK
Tel. +44 1582 544 500 Fax: +44 1582 544 501
Technical Helpline +44 1582 544 548